SL

Item Image

## making connections beautifully

**Dimensions** 

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## **BCMFT22PB-B**

Bloomsbury Chamfered Medium Oak 2 gang 20AX 2 Way Toggle Polished Brass Fluted Dome/Black Collar

Wiring

Hamilton Bloomsbury Chamfered Edge Fluted Dome Primary Range Bloomsbury Fluted Dome Insert Type 2 gang 20AX 2 Way Toggle Plate Finish Bloomsbury Chamfered Medium Oak Insert Colour Polished Brass/Black Collar EAN13 Barcode 5028690015864 Dimensions (Nominal) Double: Height = 154.0mm Width = 88.0mm Depth = 14.5mm Plinth, Collar and Dome Depth = 45.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 25mm Switched Poles Single **Current Rating** 20AX 220/250V AC Voltage 20 Amp inductive Maximum Load Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 **Terminal Capacity 3** 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand **Terminal Capacity 5** 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C

All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T +444 (0)1747 860088 F +444 (0)1179 710414
Repistered Office 1 Bushmills Bedford Road, Northampton NN4 7Y

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

All products listed conform to current British or

European standard and the product information is

correct at the time of going to press.

Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.

Recommended Location

Maximum Installation Altitude

Standard/Approval

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

Internal Use Only

BS EN 60669-1

2000m









It is the policy of the company to improve products

as part of our development programme

Therefore, we reserve the right to alter designs and dimensions without prior notice.



Correct as at 12 October 2018 04:29 PM

