Hamilton

BLOOMSBURY Chamfered Medium Oak 4 gang 20AX 2 Way Togg Item Image Wiring Image Image Image	gle Polished Brass Plain Dome/White Collar Dimensions Hemilton Bloomsbury Chamfered Edge Plain Dome 24wy Toggle	
Bloomsbury Chamfered Medium Oak 4 gang 20AX 2 Way Togg Item Image Wiring Image Image Image	Dimensions Hemilton Bloomsbury Chamfered Edge Plain Dome 124 2 Way Toggle	
Item Image Wiring Image Image	Dimensions Hemilton Bloomsbury Chamfered Edge Plain Dome 124 2 Way Toggle	
Item Image Wiring Image Item Image Image Image	Dimensions Hemilton Bloomsbury Chamfered Edge Plain Dome 124 2 Way Toggle	
Primary Range Bloomsbury Plain Dome Insert Type 4 gang 20AX 2 Way Toggle Plate Finish Bloomsbury Chamfered Medium Oak	Hamilton Bloomsbury Chamfered Edge Plain Dome 124 2 Way Toggle	
Insert Type 4 gang 20AX 2 Way Toggle Plate Finish Bloomsbury Chamfered Medium Oak	Bloomsbury Chamfered Edge Plain Dome T24 2 Way Toggle	
Insert Type 4 gang 20AX 2 Way Toggle Plate Finish Bloomsbury Chamfered Medium Oak	15.0 In the second sec	
Plate Finish Bloomsbury Chamfered Medium Oak		
Insert Colour Polished Brass/White Collar	Polished Brass/White Collar	
EAN13 Barcode 5028690126881		
Dimensions (Nominal) Quad: Height = 163mm Width = 163mm	Quad: Height = 163mm Width = 163mm Depth = 14.5mm Plinth, Collar and Dome Depth = 45.0mm	
Fixing Hole Centres Box Fixing = 120.6mm x 2 Grid Fixing = N/A	Box Fixing = 120.6mm x 2 Grid Fixing = N/A	
Minimum Wall Box Depth 25mm	25mm	
Switched Poles Single	Single	
Current Rating 20AX	20AX	
Voltage 220/250V AC		
Maximum Load 20 Amp inductive		
Mains Frequency 50Hz		
IP Rating IP2XD		
Contact Gap Minimum 3mm		
Terminal Capacity 1 5 x 1mm2		
Terminal Capacity 2 4 x 1.5mm2		
Terminal Capacity 3 2 x 2.5mm2		
Terminal Capacity 4 2 x 4mm2 Multi-strand		
Terminal Capacity 5 1 x 6mm2	1 x 6mm2	
Earth Terminal Capacity 1 6 x 1mm2	6 x 1mm2	
Earth Terminal Capacity 2 5 x 1.5mm2		
Earth Terminal Capacity 3 3 x 2.5mm2	3 x 2.5mm2	
Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	2 x 4mm2 Multi-strand	
Earth Terminal Capacity 5 1 x 6mm2	1 x 6mm2	
Product Class 1 Must be earthed		
Ambient Operating Temperature -5° to +40°C		
Recommended Location Internal Use Only		
Maximum Installation Altitude 2000m		
Standard/Approval BS EN 60669-1		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.		
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cc guarantee an exact colour match and sha of certain finishes. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ State 100 minutes and sha of certain finishes.		

R Hamilton & Co Ltd, Unit 10 Carrick Business C T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com 5 Bonville Road, Brislington, Bristol, BS4 5NZ Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

