

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


BOAFT24AB-B

Bloomsbury Ovolo Antique Mahogany 4 gang 20AX 2 Way Toggle Antique Brass Fluted Dome/Black Collar

Item Image



Wiring



Dimensions

Hemilton Bloomsbury Ovolo Edge Fluted Dome 172 2 Way Toggle 163.0 163.0 163.0 163.0 163.0 163.0 163.0 163.0 163.0 163.0 163.0

		Box Flaing Stress Holden by Blovendour Ounce All sealth components reclosed within downs, cable will enter from the Book.	
Primary Range	Bloomsbury Fluted Dome		
Insert Type	4 gang 20AX 2 Way Toggle		
Plate Finish	Bloomsbury Ovolo Antique Mahogany		
Insert Colour	Antique Brass/Black Collar		
EAN13 Barcode	5028690311881		
Dimensions (Nominal)	Quad: Height = 163mm Width = 163mm Depth = 14.5mr	Quad: Height = 163mm Width = 163mm Depth = 14.5mm Plinth, Collar and Dome Depth = 45.0mm	
Fixing Hole Centres	Box Fixing = 120.6mm x 2 Grid Fixing = N/A		
Minimum Wall Box Depth	25mm		
Switched Poles	Single		
Current Rating	20AX		
Voltage	220/250V AC		
Maximum Load	20 Amp inductive		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Contact Gap Minimum	3mm		
Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 3	2 x 2.5mm2		
Terminal Capacity 4	2 x 4mm2 Multi-strand		
Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 1	6 x 1mm2		
Earth Terminal Capacity 2	5 x 1.5mm2		
Earth Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 4	2 x 4mm2 Multi-strand		
Earth Terminal Capacity 5	1 x 6mm2		
Product Class 1	Must be earthed		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS EN 60669-1		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 12 October 2018 04:29 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











