## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


## **BOAFT24AB-W**

Bloomsbury Ovolo Antique Mahogany 4 gang 20AX 2 Way Toggle Antique Brass Fluted Dome/White Collar

Item Image



Wiring



## **Dimensions**

## Hemilton Bloomsbury Ovolo Edge Fluted Dome T24 2 Way Toggle 163.0

		But Filling Stress Holder by Blovenbury Clone All sealth components exclosed within dozen, cable will entire from the Buck.
Primary Range	Bloomsbury Fluted Dome	
Insert Type	4 gang 20AX 2 Way Toggle	
Plate Finish	Bloomsbury Ovolo Antique Mahogany	
Insert Colour	Antique Brass/White Collar	
EAN13 Barcode	5028690312888	
Dimensions (Nominal)	Quad: Height = 163mm Width = 163mm Depth = 14.5mm Plinth, Collar and Dome Depth = 45.0mm	
Fixing Hole Centres	Box Fixing = 120.6mm x 2 Grid Fixing = N/A	
Minimum Wall Box Depth	25mm	
Switched Poles	Single	
Current Rating	20AX	
Voltage	220/250V AC	
Maximum Load	20 Amp inductive	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 3	2 x 2.5mm2	
Terminal Capacity 4	2 x 4mm2 Multi-strand	
Terminal Capacity 5	1 x 6mm2	
Earth Terminal Capacity 1	6 x 1mm2	
Earth Terminal Capacity 2	5 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	2 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-1	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 12 October 2018 04:29 PM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











