making connections beautifully


Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


BOAPT32PB-W

Bloomsbury Ovolo Antique Mahogany 2 gang 20AX Intermediate Toggle Polished Brass Plain Dome/White Collar

Item Image







	2	The Chang Grown I Address by All swifts components annoticed with absorbed by the desired components annoticed with absorbed by the desired components annoticed with a desired components annoticed with a desired components annoticed with a desired component and a desired component and a desired component annoticed with a desired component and a desired component and a desired component and a desired component annotation and a desired component annotation and a desired component a
Primary Range	Bloomsbury Plain Dome	
Insert Type	2 gang 20AX Intermediate Toggle	
Plate Finish	Bloomsbury Ovolo Antique Mahogany	
Insert Colour	Polished Brass/White Collar	
EAN13 Barcode	5028690436928	
Dimensions (Nominal)	Double: Height = 154.0mm Width = 88.0mm Depth = 14.5mm Plinth, Collar and Dome Depth = 45.0mm	
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = N/A	
Minimum Wall Box Depth	25mm	
Switched Poles	Single	
Current Rating	20AX	
Voltage	220/250V AC	
Maximum Load	20 Amp inductive	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 3	2 x 2.5mm2	
Terminal Capacity 4	2 x 4mm2 Multi-strand	
Terminal Capacity 5	1 x 6mm2	
Earth Terminal Capacity 1	6 x 1mm2	
Earth Terminal Capacity 2	5 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	2 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-1	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within	Due to manufacturing processes we cannot	Correct as at 12 October 2018 04:29 PM

guarantee an exact colour match and shadings of

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

the limitations of reproduction and printing

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84













E&OE