SL

Item Image

making connections beautifully

Dimensions

Hamilton

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

BODFT22PB-B

Bloomsbury Ovolo Dark Oak 2 gang 20AX 2 Way Toggle Polished Brass Fluted Dome/Black Collar

Wiring

Ovolo Edge T22 2 Way Toggle Primary Range Bloomsbury Fluted Dome Insert Type 2 gang 20AX 2 Way Toggle Plate Finish Bloomsbury Ovolo Dark Oak Insert Colour Polished Brass/Black Collar EAN13 Barcode 5028690195863 Dimensions (Nominal) Double: Height = 154.0mm Width = 88.0mm Depth = 14.5mm Plinth, Collar and Dome Depth = 45.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 25mm Switched Poles Single **Current Rating** 20AX 220/250V AC Voltage 20 Amp inductive Maximum Load Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 **Terminal Capacity 3** 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand **Terminal Capacity 5** 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2

Illustrations and diagrams are reproduced within Due to manu the limitations of reproduction and printing guarantee an e process and are not binding.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.

All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.

It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Correct as at 12 October 2018 04:29 PM

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

All products listed conform to current British or

European standard and the product information is

correct at the time of going to press.

Earth Terminal Capacity 4

Earth Terminal Capacity 5

Recommended Location

Maximum Installation Altitude

Standard/Approval

Ambient Operating Temperature

Product Class 1

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

2 x 4mm2 Multi-strand

1 x 6mm2

Must be earthed

BS EN 60669-1

-5° to +40°C Internal Use Only

2000m











