SL

Item Image

making connections beautifully

Dimensions

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

BOMFT22PB-W

Bloomsbury Ovolo Medium Oak 2 gang 20AX 2 Way Toggle Polished Brass Fluted Dome/White Collar

Wiring

Hamilton Ovolo Edge T22 2 Way Toggle Primary Range Bloomsbury Fluted Dome Insert Type 2 gang 20AX 2 Way Toggle Plate Finish Bloomsbury Ovolo Medium Oak Insert Colour Polished Brass/White Collar EAN13 Barcode 5028690186861 Dimensions (Nominal) Double: Height = 154.0mm Width = 88.0mm Depth = 14.5mm Plinth, Collar and Dome Depth = 45.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 25mm Switched Poles Single **Current Rating** 20AX 220/250V AC Voltage 20 Amp inductive Maximum Load Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 **Terminal Capacity 3** 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand **Terminal Capacity 5** 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2

All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

All products listed conform to current British or

European standard and the product information is

correct at the time of going to press.

Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.

Product Class 1

Standard/Approval

Ambient Operating Temperature

Recommended Location

Maximum Installation Altitude

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

Must be earthed

BS EN 60669-1

-5° to +40°C Internal Use Only

2000m









It is the policy of the company to improve products

as part of our development programme

Therefore, we reserve the right to alter designs and dimensions without prior notice.



Correct as at 12 October 2018 04:30 PM

