## Hamilto

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio **BOMPTDPBC-B** Bloomsbury Ovolo Medium Oak 1 gang 20AX Double Pole Toggle Bright Chrome Plain Dome/Black Collar Item Image Wiring Dimensions Hamilton Ble TDP Double Pole Toggle 0 88.0 ..... Earth 60.3 Live Bloomsbury Plain Dome Primary Range Insert Type 1 gang 20AX Double Pole Toggle Plate Finish Bloomsbury Ovolo Medium Oak Insert Colour Bright Chrome/Black Collar EAN13 Barcode 5028690343912 Dimensions (Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 14.5mm Plinth, Collar and Dome Depth = 45.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 25mm Switched Poles Double Current Rating 20AX 220/250V AC Voltage 20 Amp inductive Maximum Load Mains Frequency 50Hz IP2XD IP Rating Contact Gap Minimum 3mm **Terminal Capacity 1** 5 x 1mm2 **Terminal Capacity 2** 4 x 1.5mm2 **Terminal Capacity 3** 2 x 2.5mm2 **Terminal Capacity 4** 2 x 4mm2 Multi-strand **Terminal Capacity 5** 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Internal Use Only **Recommended Location** Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. All products listed conform to current British or It is the policy of the company to improve products European standard and the product information is as part of our development programme correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Correct as at 12 October 2018 04:30 PM Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Illustrations and diagrams are reproduced within the limitations of reproduction and printing E&OE process and are not binding of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com E info

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84



SL