


Wiring Accessories • Circuit Protection • Lighting Control & Multi-room Audio

ELMSS2GY

Elemento Grey IP66 2 gang Enclosure fitted with a Double 13 Amp Switched Socket.





Dimensions

Primary Range Elemento		
Plate Finish	Primary Range	Elemento
Insert Colour		
EAN13 Barcode 505275050203 Dimensions (Nominal) (W) 170mm (H) 153mm (D) 95mm Weight Fixing Hole Centres Fixing Hole Centres 120.6mm Minimum Wall Box Depth N/A Switched Poles Double Pole Current Rating 13 Amp Voltage 220 / 250V AC Maximum Load 13 Amp Mains Frequency Total Capacity Ample Contact Gap Minimum 3mm Terminal Capacity 1 4 x 2.5mm² Terminal Capacity 2 3 x 4mm² Terminal Capacity 3 2 x 6mm² Multi-stranded Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 2 3 x 4mm² Earth Terminal Capacity 3 2 x 6mm² Multi-Strand Earth Terminal Capacity 4 1 x 1mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval IP66 & BS1363-2 Additional Notes Dual Earth: Yes	Plate Finish	High Grade Thermoset Plastic
Dimensions (Nominal) Weight Fixing Hole Centres 120.6mm Minimum Wall Box Depth N/A Switched Poles Double Pole Current Rating 13 Amp Voltage 220 / 250V AC Maximum Load Mains Frequency Contact Gap Minimum 3mm Terminal Capacity 1 4 x 2.5mm² Terminal Capacity 2 3 x 4mm² Terminal Capacity 3 1 x 10mm² Earth Terminal Capacity 4 4 x 2.5mm² Earth Terminal Capacity 1 4 x 2.5mm² Earth Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 3 1 x 4mm² Earth Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 4 1 x 1mm² Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval Additional Notes Dual Earth: Yes	Insert Colour	Grey / White Accessory
Weight Fixing Hole Centres 120.6mm Minimum Wall Box Depth N/A Switched Poles Double Pole Current Rating 13 Amp Voltage 220 / 250V AC Maximum Load 13 Amp Mains Frequency 13 Amp Contact Gap Minimum 3mm Terminal Capacity 1 4 x 2.5mm² Terminal Capacity 2 3 x 4mm² Terminal Capacity 3 2 x 6mm² Multi-stranded Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 1 4 x 2.5mm² Earth Terminal Capacity 2 3 x 4mm² Earth Terminal Capacity 3 2 x 6mm² Multi-Strand Earth Terminal Capacity 4 1 x 1mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval IP66 & BS1363-2 Additional Notes Dual Earth: Yes	EAN13 Barcode	505275050203
Fixing Hole Centres	Dimensions (Nominal)	(W) 170mm (H) 153mm (D) 95mm
Minimum Wall Box Depth N/A Switched Poles Double Pole Current Rating 13 Amp Voltage 220 / 250V AC Maximum Load 13 Amp Mains Frequency Image: Contact Gap Minimum Contact Gap Minimum 3mm Terminal Capacity 1 4 x 2.5mm² Terminal Capacity 2 3 x 4mm² Terminal Capacity 3 2 x 6mm² Multi-stranded Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 1 4 x 2.5mm² Earth Terminal Capacity 3 2 x 6mm² Multi-Strand Earth Terminal Capacity 4 1 x 1mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval IP66 & BS1363-2 Additional Notes Dual Earth: Yes		
Switched PolesDouble PoleCurrent Rating13 AmpVoltage220 / 250V ACMaximum Load13 AmpMains Frequency13 AmpContact Gap Minimum3mmTerminal Capacity 14 x 2.5mm²Terminal Capacity 23 x 4mm²Terminal Capacity 32 x 6mm² Multi-strandedTerminal Capacity 41 x 10mm²Earth Terminal Capacity 14 x 2.5mm²Earth Terminal Capacity 23 x 4mm²Earth Terminal Capacity 32 x 6mm² Multi-StrandEarth Terminal Capacity 41 x 1mm²Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalIP66 & BS1363-2Additional NotesDual Earth: Yes		120.6mm
Current Rating 13 Amp Voltage 220 / 250V AC Maximum Load 13 Amp Mains Frequency	Minimum Wall Box Depth	N/A
Voltage 220 / 250V AC Maximum Load 13 Amp Mains Frequency Contact Gap Minimum 3mm Terminal Capacity 1 4 x 2.5mm² Terminal Capacity 2 3 x 4mm² Terminal Capacity 3 2 x 6mm² Multi-stranded Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 1 4 x 2.5mm² Earth Terminal Capacity 2 3 x 4mm² Earth Terminal Capacity 2 3 x 4mm² Earth Terminal Capacity 3 2 x 6mm² Multi-Strand Earth Terminal Capacity 3 1 x 1mm² Earth Terminal Capacity 4 1 x 1mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval IP66 & BS1363-2 Additional Notes Dual Earth: Yes	Switched Poles	Double Pole
Maximum Load Mains Frequency Contact Gap Minimum Terminal Capacity 1 4 x 2.5mm² Terminal Capacity 2 3 x 4mm² Terminal Capacity 3 2 x 6mm² Multi-stranded Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 1 4 x 2.5mm² Earth Terminal Capacity 2 3 x 4mm² Earth Terminal Capacity 3 2 x 6mm² Multi-Strand Earth Terminal Capacity 2 3 x 4mm² Earth Terminal Capacity 3 2 x 6mm² Multi-Strand Earth Terminal Capacity 4 1 x 1mm² Product Class 1 Ambient Operating Temperature Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval IP66 & BS1363-2 Additional Notes Dual Earth: Yes	Current Rating	13 Amp
Mains Frequency Contact Gap Minimum 3mm Terminal Capacity 1		220 / 250V AC
Contact Gap Minimum3mmTerminal Capacity 14 x 2.5mm²Terminal Capacity 23 x 4mm²Terminal Capacity 32 x 6mm² Multi-strandedTerminal Capacity 41 x 10mm²Earth Terminal Capacity 14 x 2.5mm²Earth Terminal Capacity 23 x 4mm²Earth Terminal Capacity 32 x 6mm² Multi-StrandEarth Terminal Capacity 41 x 1mm²Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalIP66 & BS1363-2Additional NotesDual Earth: Yes	Maximum Load	13 Amp
Terminal Capacity 1 4 x 2.5mm² Terminal Capacity 2 3 x 4mm² Terminal Capacity 3 2 x 6mm² Multi-stranded Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 1 4 x 2.5mm² Earth Terminal Capacity 2 3 x 4mm² Earth Terminal Capacity 2 3 x 4mm² Earth Terminal Capacity 3 2 x 6mm² Multi-Strand Earth Terminal Capacity 4 1 x 1mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval IP66 & BS1363-2 Additional Notes Dual Earth: Yes	Mains Frequency	
Terminal Capacity 2 Terminal Capacity 3 Z x 6mm² Multi-stranded Terminal Capacity 4 Larth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Product Class 1 Must be earthed Ambient Operating Temperature Ambient Operating Temperature Fecommended Location Internal Use Only Maximum Installation Altitude Must be SS1363-2 Additional Notes A 4 x 2.5mm² A x 2.5mm² A x 4mm² A x 1 mm² A x 1		3mm
Terminal Capacity 3 Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval Additional Notes Dual Earth: Yes	Terminal Capacity 1	4 x 2.5mm ²
Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 1 4 x 2.5mm² Earth Terminal Capacity 2 3 x 4mm² Earth Terminal Capacity 3 2 x 6mm² Multi-Strand Earth Terminal Capacity 4 1 x 1mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval IP66 & BS1363-2 Additional Notes Dual Earth: Yes	Terminal Capacity 2	3 x 4mm ²
Earth Terminal Capacity 1 4 x 2.5mm² Earth Terminal Capacity 2 3 x 4mm² Earth Terminal Capacity 3 2 x 6mm² Multi-Strand Earth Terminal Capacity 4 1 x 1mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval IP66 & BS1363-2 Additional Notes Dual Earth: Yes	Terminal Capacity 3	2 x 6mm² Multi-stranded
Earth Terminal Capacity 2 3 x 4mm² Earth Terminal Capacity 3 2 x 6mm² Multi-Strand Earth Terminal Capacity 4 1 x 1mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval IP66 & BS1363-2 Additional Notes Dual Earth: Yes	Terminal Capacity 4	1 x 10mm ²
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Product Class 1 Ambient Operating Temperature Recommended Location Must be earthed -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval Additional Notes Dual Earth: Yes	Earth Terminal Capacity 1	4 x 2.5mm ²
Earth Terminal Capacity 4 1 x 1mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40° C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval IP66 & BS1363-2 Additional Notes Dual Earth: Yes	Earth Terminal Capacity 2	3 x 4mm ²
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval IP66 & BS1363-2 Additional Notes Dual Earth: Yes		2 x 6mm² Multi-Strand
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval IP66 & BS1363-2 Additional Notes Dual Earth: Yes	Earth Terminal Capacity 4	1 x 1mm ²
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval IP66 & BS1363-2 Additional Notes Dual Earth: Yes	Product Class 1	Must be earthed
Maximum Installation Altitude 2000m Standard/Approval IP66 & BS1363-2 Additional Notes Dual Earth: Yes	Ambient Operating Temperature	-5° to +40°C
Standard/Approval IP66 & BS1363-2 Additional Notes Dual Earth: Yes	Recommended Location	Internal Use Only
Additional Notes Dual Earth: Yes	Maximum Installation Altitude	2000m
	Standard/Approval	IP66 & BS1363-2
Patents and Trademarks	Additional Notes	Dual Earth: Yes
	Patents and Trademarks	

British or European standard and the product information is correct at the time of going to press.

British or European standard and the product information is correct at the time of going to press.

Calliustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.

Calliustrations are manufacturing an accredited. BS EN ISO 9001: 2015 products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Correct at August 2018

All accessories are manufactured under

R Hamilton & Co Ltd • Unit 10 Carrick Business Centre • 4-5 Bonville Road • Brislington • Bristol • BS4 5NZ T: +44 (0)1747 860088 • F: +44 (0)179 418713 • E: info@hamilton-litestat.com



All products listed conform to current









It is the policy of the company to improve

