Hamilton

making connections beautifully

	Wiring Accessories • Circuit Protection • Sn	har engining control a Hala-room Addio
	IDPBL-B	
Grid	d-IT 20AX Double Pole Rocker Module Black/	/Black
Item Image	Wiring	Dimensions
	Live Noutral N N L N L N BS EN 60669 20X 250V- Double Pole L OUT N Live Nottral To To Load Load	
Primary Range	GRID-IT	
nsert Type	20AX Double Pole Rocker Module	
Plate Finish	GRID-IT Module No Plate Colour	
nsert Colour	Black/Black	
EAN13 Barcode	5051164059637	
Veight	43 GR	
Switched Poles	Double	
Current Rating	20AX	
/oltage	220/250V AC	
/laximum Load	20 Amp inductive	
lains Frequency	50Hz	
P Rating	IP2XD	
Contact Gap Minimum	3mm	
erminal Capacity 1	5 x 1mm2	
erminal Capacity 2	4 x 1.5mm2	
erminal Capacity 3	2 x 2.5mm2	
erminal Capacity 4	1 x 4mm2 Multi-strand	
erminal Capacity 5	1 x 6mm2	
arth Terminal Capacity 1	6 x 1mm2	
arth Terminal Capacity 2	5 x 1.5mm2	
arth Terminal Capacity 3	3 x 2.5mm2	
arth Terminal Capacity 4	2 x 4mm2 Multi-strand	
arth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Face plate must be earthed	
mbient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Aximum Installation Altitude	2000m	
tandard/Approval	BS EN 60669-1	
Advalle Size All products listed conform to current British or European standard and the product information is correct at the time of going to press.	Height = 51mm Width = 23mm Depth = 21mm All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:54 E8
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville F	of certain finishes.	Listed in Strimble LUCKINS riba roduct selector CSCPus CSC

SL