## Hamilton

## making connections beautifully

		art Lighting Control & Multi-room Audio
	IDPFNWH-W	
Grid-IT 20	AX Double Pole Rocker Module Fan Symbol V	Vhite/White
Item Image	Wiring	Dimensions
Contraction of the second seco	Live Neutral N IN L N N CC BS EN 80669 20AX 250V- Double Pole L OUT N Live Neutral To To Load Load	
Primary Range	GRID-IT	
nsert Type	20AX Double Pole Rocker Module + Printed Legend	
Plate Finish	GRID-IT Module No Plate Colour	
nsert Colour	White/White	
EAN13 Barcode	5017504070489	
Veight	43 GR	
Switched Poles	Double	
Current Rating	20AX	
/oltage	220/250V AC	
Maximum Load	20 Amp inductive	
Mains Frequency	50Hz	
P Rating	IP2XD	
Contact Gap Minimum	3mm	
erminal Capacity 1	5 x 1mm2	
Ferminal Capacity 2	4 x 1.5mm2	
erminal Capacity 3	2 x 2.5mm2	
erminal Capacity 4	1 x 4mm2 Multi-strand	
erminal Capacity 5	1 x 6mm2	
arth Terminal Capacity 1	6 x 1mm2	
arth Terminal Capacity 2	5 x 1.5mm2	
arth Terminal Capacity 3	3 x 2.5mm2	
arth Terminal Capacity 4	2 x 4mm2 Multi-strand	
arth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Face plate must be earthed	
mbient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
faximum Installation Altitude	2000m	
tandard/Approval	BS EN 60669-1	
1odule Size	Height = 51mm Width = 23mm Depth = 21mm	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:54 E&

SL