## Hamilton

## making connections beautifully

	Wiring Accessories • Circuit Protection • Sr	mart Lighting Control & Multi-room Audio
	IDPHOWH-W	
Grid-II	20AX Double Pole Rocker Module Hob Whi	te/White
Item Image	Wiring	Dimensions
Hob	Live Neutral IN IN L IN N C BS EN 60699 20AX 250V- Double Pole L OUT N Live Neutral Live Neutral Load Load	
Primary Range	GRID-IT	
nsert Type	20AX Double Pole Rocker Module + Printed Legend	
Plate Finish	GRID-IT Module No Plate Colour	
nsert Colour	White/White	
AN13 Barcode	5017504070557	
Veight witched Poles	43 GR Double	
Current Rating	20AX 220/250V AC	
Aaximum Load	20 Amp inductive 50Hz	
Aains Frequency		
P Rating	IP2XD	
Contact Gap Minimum	3mm	
erminal Capacity 1	5 x 1mm2	
erminal Capacity 2	4 x 1.5mm2	
erminal Capacity 3	2 x 2.5mm2	
erminal Capacity 4	1 x 4mm2 Multi-strand	
erminal Capacity 5	1 x 6mm2	
arth Terminal Capacity 1	6 x 1mm2	
arth Terminal Capacity 2	5 x 1.5mm2	
arth Terminal Capacity 3	3 x 2.5mm2	
arth Terminal Capacity 4	2 x 4mm2 Multi-strand	
arth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Face plate must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Naximum Installation Altitude	2000m	
itandard/Approval	BS EN 60669-1	
<i>I</i> odule Size	Height = 51mm Width = 23mm Depth = 21mm	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:54 E&
process and are not binding. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville R T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered (	of certain finishes.	Listed in Mitzer LUCKINS riba rocluct selector

SL