Hamilton

making connections beautifully

	Wiring Accessories • Circuit Protection • Sm	art Lighting Control & Multi-room Audio
	IDPHTBL-B	
Grid-IT	20AX Double Pole Rocker Module Heater Bla	ck/Black
Item Image	Wiring	Dimensions
	Live Neutral	
Heater	Live Notifal N IN L IN N CE BS EN 60669 20AX 250V- Double Pole L OUT N Live Neitral To Load Load	
Primary Range	GRID-IT	
nsert Type	20AX Double Pole Rocker Module + Printed Legend	
Plate Finish	GRID-IT Module No Plate Colour	
	Black/Black	
nsert Colour		
AN13 Barcode	5017504070564	
Veight	30 GR	
witched Poles	Double	
Current Rating	20AX	
/oltage	220/250V AC	
Naximum Load	20 Amp inductive	
lains Frequency	50Hz	
P Rating	IP2XD	
Contact Gap Minimum	3mm	
erminal Capacity 1	5 x 1mm2	
erminal Capacity 2	4 x 1.5mm2	
erminal Capacity 3	2 x 2.5mm2	
erminal Capacity 4	1 x 4mm2 Multi-strand	
erminal Capacity 5	1 x 6mm2	
arth Terminal Capacity 1	6 x 1mm2	
arth Terminal Capacity 2	5 x 1.5mm2	
arth Terminal Capacity 3	3 x 2.5mm2	
arth Terminal Capacity 4	2 x 4mm2 Multi-strand	
arth Terminal Capacity 5	1 x 6mm2	
roduct Class 1	Face plate must be earthed	
mbient Operating Temperature	-5° to +40°C	
ecommended Location	Internal Use Only	
laximum Installation Altitude	2000m	
tandard/Approval	BS EN 60669-1	
lodule Size	Height = 51mm Width = 23mm Depth = 21mm	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:54 Et

SL