SL

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## **IDPTDBL-B**

Grid-IT 20AX Double Pole Rocker Module Tumble Dryer Black/Black

| Grid-11 ZUAX Double Pole Rocker Module 1 umble Dryer Black/Black |   |            |
|--|---|------------|
| Item Image   | Wiring  | Dimensions |
| Tumble Dryer   | Live Neutral IN IN  C C C BS EN 60669 20AX 250V- Double Pole Lout Neutral To To Load Load |            |
| Primary Range  | GRID-IT   |            |
| Insert Type  | 20AX Double Pole Rocker Module + Printed Legend   |            |
| Plate Finish   | GRID-IT Module No Plate Colour  |            |
| Insert Colour  | Black/Black   |            |
| EAN13 Barcode  | 5017504070694   |            |
| Weight   | 43 GR   |            |
| Switched Poles   | Double  |            |
| Current Rating   | 20AX  |            |
| Voltage  | 220/250V AC   |            |
| Maximum Load   | 20 Amp inductive  |            |
| Mains Frequency  | 50Hz  |            |
| IP Rating  | IP2XD   |            |
| Contact Gap Minimum  | 3mm   |            |
| Terminal Capacity 1  | 5 x 1mm2  |            |
| Terminal Capacity 2  | 4 x 1.5mm2  |            |
| Terminal Capacity 3  | 2 x 2.5mm2  |            |
| Terminal Capacity 4  | 1 x 4mm2 Multi-strand   |            |
| Terminal Capacity 5  | 1 x 6mm2  |            |
| Earth Terminal Capacity 1  | 6 x 1mm2  |            |
| Earth Terminal Capacity 2  | 5 x 1.5mm2  |            |
| Earth Terminal Capacity 3  | 3 x 2.5mm2  |            |
| Earth Terminal Capacity 4  | 2 x 4mm2 Multi-strand   |            |
| Earth Terminal Capacity 5  | 1 x 6mm2  |            |
| Product Class 1  | Face plate must be earthed  |            |
| Ambient Operating Temperature                                    | -5° to +40°C  |            |
| Recommended Location   | Internal Use Only   |            |
| Maximum Installation Altitude                                    | 2000m   |            |
| Standard/Approval  | BS EN 60669-1   |            |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

All products listed conform to current British or

European standard and the product information is

correct at the time of going to press.

Illustrations and diagrams are reproduced within

the limitations of reproduction and printing

process and are not binding.

Module Size

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

Height = 51mm Width = 23mm Depth = 21mm

All accessories are manufactured under an accredited

BS EN ISO 9001: 2015 Quality Management System.

Due to manufacturing processes we cannot

guarantee an exact colour match and shadings of







It is the policy of the company to improve products

as part of our development programme.

Therefore, we reserve the right to alter designs

and dimensions without prior notice.



Correct as at 15 October 2018 09:54 AM



E&OE