## Hamilton

## making connections beautifully

	Wining Accessories • Circuit Protection • Sr	nart Lighting Control & Multi-room Audio
IDTESB		
Grid-IT 250W/210VA Multi-Way Trailing Edge Push On/Off Dimmer Module and Knob Kit Satin Brass		
Ghu-11 23000/210VA Multi-V		
Item Image	Wiring	Dimensions
	Hutis Way Wiring using Retractive PTM Rocker Switches Interview of the state of th	
Primary Range	GRID-IT	
Insert Type	250W/210VA Multi-Way Trailing Edge Push On/Off Dimmer Module and Knob Kit	
Plate Finish	GRID-IT Module No Plate Colour	
Insert Colour	Satin Brass	
EAN13 Barcode	5051164099237	
Wattage	250W Resistive 210VA Inductive	
Switched Poles	Single	
Current Rating	1.1 Amp	
Voltage	220/250V AC	
Maximum Load	250W Resistive 210VA Inductive Min Load 25W/25VA	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	None	
Terminal Capacity 1	2 x 1mm2	
Terminal Capacity 2	2 x 1.5mm2	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 1	4 x 1.5mm2	
	4 x 1.5mm2 3 x 2.5mm2	
Earth Terminal Capacity 3	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 4		
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Face plate must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-2-1	
Additional Notes	TRAILING EDGE TECHNOLOGY DIMMERS. Are suitable for control of both resistive and inductive loads. When used for dimming low voltage electronic halogen transformers it must be noted that the dimmer controls the primary side of the transformer. Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. When using mains voltage halogen load transformer - maximum rating is 210VA. NOTE: For multi-way switching a push to make retractive switch should be installed in the other positions.	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:54 AM E&OE
	ad, Brislington, Bristol, BS4 5NZ fice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84	Listed in Strimble LUCKINS Riccor Discrete selector CER In Strike

IDTESB - Grid-IT 250W/210VA Multi-Way Trailing Edge Push On/Off Dimmer Module and Knob Kit Satin Brass

SL