Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio **IDTSSB-B** Grid-IT Multi-Way Touch Slave Controller Module Satin Brass/Black Item Image Wiring Dimensions Multi- Way Wiring using Slave module(s) φφσ i 5 Lamp Neutra SLAVE MODULE ULE IS USED PER SLAVE MODUL GRID-IT Primary Range Insert Type Multi-Way Touch Slave Controller Module Plate Finish **GRID-IT Module No Plate Colour** Insert Colour Satin Brass/Black EAN13 Barcode 5051164099251 Wattage The same as Touch Master or Ceiling Dimmer Switched Poles N/A Current Rating The same as Touch Master or Ceiling Dimmer Voltage 220/250V AC The same as Touch Master Maximum Load Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum N/A **Terminal Capacity 1** 2 x 1mm2 **Terminal Capacity 2** 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be Additional Notes used with Touch Master Dimmers All products listed conform to current British or All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products European standard and the product information is as part of our development programme correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Illustrations and diagrams are reproduced within Correct as at 15 October 2018 09:54 AM the limitations of reproduction and printing E&OE process and are not binding. of certain finishes. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ Listed in STrimble SECA T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YE Registered in London No. 941624 VAT Registration No. 222 6607 84 nton NN4 7YE LUCKINS

SL