SL

making connections beautifully

the limitations of reproduction and printing guarantee an exact colour match and shadings of E8	Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio			
Item Image Wiring Dimensions Primary Range ORID-IT Insert Type 20AX Double Pole Key Switch Module Plate Finish GRID-IT Module No Plate Colour Insert Colour Phate Finish GRID-IT Module No Plate Colour Phate Colour Colour Phate Grid Module GRID-IT Module No Plate Colour Phate Colour Phate Colour GRID-IT Module No Plate Colour Phate Colour Phate Colour GRID-IT Module No Plate Colour Phate Colour GRID-IT Module No Plate Colour Phate Colour Phate Colour GRID-IT Module No Plate Colour Phate Colour Phate Colour GRID-IT Module No Plate Colour GRID-IT Module Colour GRID-IT Module Phate Colour GRID-IT Module Colour All Module Colour All Module Colour Grid Module Star All Rocescoines are manufactured under an associated of Phate Colour on Colour on Colour Plate Colour All Rocescoines are manufactured under an associated of Phate Colour on Colour on Colour Plate Colour All Rocescoines are manufactured under and standing of Colour Start Col	IKDPW			
Item Image Wiring Dimensions Primary Range ORID-IT Insert Type 20AX Double Pole Key Switch Module Plate Finish GRID-IT Module No Plate Colour Insert Colour Phate Finish GRID-IT Module No Plate Colour Phate Colour Colour Phate Grid Module GRID-IT Module No Plate Colour Phate Colour Phate Colour GRID-IT Module No Plate Colour Phate Colour Phate Colour GRID-IT Module No Plate Colour Phate Colour GRID-IT Module No Plate Colour Phate Colour Phate Colour GRID-IT Module No Plate Colour Phate Colour Phate Colour GRID-IT Module No Plate Colour GRID-IT Module Colour GRID-IT Module Phate Colour GRID-IT Module Colour All Module Colour All Module Colour Grid Module Star All Rocescoines are manufactured under an associated of Phate Colour on Colour on Colour Plate Colour All Rocescoines are manufactured under an associated of Phate Colour on Colour on Colour Plate Colour All Rocescoines are manufactured under and standing of Colour Start Col	Grid-IT 20AX Double Pole Key Switch Module White/White			
Primary Range GRID-IT Insert Type JOAN Coulsie Pele Key Switch Module Plate Finish GRID-IT Module No Piste Colour Insert Colour White White EAN13 Barcode JOSS 1664159377 Weight JOSS 6R Weight JOSS 7 W	Ond-11 ZOAX Bouble I die Ney Switch Module White			
Primary Range GRID-IT Insert Type 20AX Double Pole Key Switch Module Insert Type 20AX Double Pole Key Switch Module GRID-IT Module No Piste Colour Insert Co	Item Image	Wiring	Dimensions	
Insert Type 20AX Double Pole Key Switch Module Plate Finish GRID-IT Module No Plate Colour White/White EAN13 Barcode 5051164159337 Weight 35 GR Switched Poles Double Current Rating 20AX Voltage 220/250V AC Maximum Load Maximu		BS EN 60669 20AX 250V- Double Pole L OUT N OUT N Notitral To To		
Plate Finish GRID-IT Module No Plate Colour Insert Colour White SAN1's Barcode So51's Id-s159337 Weight 35 GR Switched Poles Double Current Rating 20AX Voltage 220'250V AC Maximum Load 20 Amp inductive Mains Frequency IP Rating IP2XD Contact Gap Minimum 3mm Preminal Capacity 1 Ferminal Capacity 1 Ferminal Capacity 1 Ferminal Capacity 3 1 x 4mm2 Multi-strand Terminal Capacity 1 Ferminal Capacity 1 Ferminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 1 Ferminal Capacity 1 Ferminal Capacity 1 Ferminal Capacity 3 2 x 2.5mm2 Sarth Terminal Capacity 1 Ferminal Capacity 4 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 6 Ferminal Capacity 1 Ferminal Capacity 3 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 6 Ferminal Capacity 6 Ferminal Capacity 6 Ferminal Capacity 8 Ferminal Capacity 8 Terminal Capacity 9 Termina	Primary Range	GRID-IT		
Insert Colour WhiteWhite EAN13 Barcode 5051164159337 Weight 35 GR Switched Poles Double Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 2 1 x 4mm2 Multi-strand Terminal Capacity 3 1 x 4mm2 Multi-strand Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 7 5 x 4mm2 Multi-strand Earth Terminal Capacity 8 5 x 1.5mm2 Earth Terminal Capacity 8 5 x 1.5mm2 Earth Terminal Capacity 9 5 x 2.5mm2 Earth Terminal Capacity 9 5 x 4.5mm2 Earth Terminal Capacity 9 5 x 1.5mm2 Earth Terminal Capacity 9 5 x 4.5mm2 Earth Terminal Capacit	Insert Type	20AX Double Pole Key Switch Module		
EAN13 Barcode 5051184159337 Weight 35 GR Switched Poles Double Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 1 x 4mm2 Multi-strand Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 7 5 x 1.5mm2 Earth Terminal Capacity 8 5 x 1.5mm2 Earth Terminal Capacity 9 x 1 x 6mm2 Eart	Plate Finish	GRID-IT Module No Plate Colour		
Weight 35 GR Switched Poles Double Double Current Rating 20AX	Insert Colour	White/White		
Switched Poles Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Forduct Class 1 Face plate must be earthed Ambient Operating Temperature Forduct Class 1 Face plate must be earthed Ambient Operating Temperature Recommended Location Maximum Installation Altitude Standard/Approval BS EN 16069-1 Height = 51mm Width = 23mm Depth = 21mm All products lated conform to current British or European standard and the product information is correct at the time of going to press. But the Imitations of reproduction and printing of the company to improve products and dimensions without prior notice. All accessories are manufactured under an accredited BS EN 150 9001 ± 215 Quality Management System. But the imitations of reproduction and reproduct or manufacturing processes we cannot be the imitations of reproduction and printing of guarantee an exact colour match and shadings of E8	EAN13 Barcode	5051164159337		
Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 7 5 x 1.5mm2 Earth Terminal Capacity 8 7 x 1.5mm2 Earth Terminal Capacity 9 5 x 1.5mm2 Earth Terminal Capacity 9 5 x 1.5mm2 Earth Terminal Capacity 9 7 x 1.5mm2 Earth Terminal Capacity 9 7 x 1.5mm2 Earth Terminal Capacity 9 7 x 1.5mm2 Earth Terminal Capacity 9 8 x 1.5mm2 Earth Terminal Capacity 9	Weight	35 GR		
Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IPZXD Contact Gap Minimum 3mm Terminal Capacity 1 5.1 mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 1 5 1 x 6mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 9	Switched Poles	Double		
Maximum Load 20 Amp inductive	Current Rating	20AX		
Mains Frequency Pasting P2XD	Voltage			
IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Face plate must be earthed Ambient Operating Temperature 5 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Module Size Height = 51mm Width = 23mm Depth = 21mm All products listed conform to current British or European standard and the product information is correct at the time of going to press. B SEN 50 9001 : 2015 Quality Management System. Therefore, we reserve the right to after designs and dimensions without prior notice. Therefore, we reserve the right to after designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of E8	Maximum Load			
Contact Gap Minimum Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 5 1 x 6mm2 Found Learn Lear	Mains Frequency			
Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Recommended Location	IP Rating			
Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 6 Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 2 Terminal Capacity 2 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 Terminal Capacity 4 Terminal Capacity 5 Terminal Capacity 6 Terminal Capacity 6 Terminal Capacity 8 Terminal Capacity 9 Terminal	Contact Gap Minimum	3mm		
Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 To multi-strand Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Module Size All products listed conform to current British or European standard and the product information is correct at the time of going to press. BE N ISO 9001 : 2015 Quality Management System. BUB to manufacturing processes we cannot the limitations of reproduction and printing Examples of the manufacturing processes we cannot guarantee an exact colour match and shadings of Examples of the company to improve products and dimensions without prior notice. Examples of the multi-strand shadings of the company to improve products and dimensions without prior notice. Examples of the multi-strand shadings of the company to improve products and dimensions without prior notice. Examples of the multi-strand shadings of the company to improve products and dimensions without prior notice. Examples of the multi-strand shadings of the company to improve products and dimensions without prior notice. Examples of the multi-strand shadings of the company to improve products and dimensions without prior notice. Examples of the multi-strand shadings of the company to improve products and shadings of the company to improve product	Terminal Capacity 1			
Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 6 Terminal Capacity 7 Terminal Capacity 8 Terminal Capacity 8 Terminal Capacity 9 Termin	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 9	Terminal Capacity 3	2 x 2.5mm2		
Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Module Size Height = 51mm Width = 23mm Depth = 21mm All products listed conform to current British or European standard and the product information is correct at the time of going to press. Blustrations and diagrams are reproduced within the limitations of reproduction and printing quarantee an exact colour match and shadings of Correct as at 15 October 2018 09:54 E8	Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Module Size All products listed conform to current British or European standard and the product information is correct at the time of going to press. All uscessories are manufactured under an accredited BS EN 150 9001: 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of E8	Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1 Module Size All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products as a part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. But to manufacturing processes we cannot guarantee an exact colour match and shadings of Earth Terminal Capacity 4 2 x 4mm2 Multi-strand 1 x 6mm2 Product Class 1 Face plate must be earthed -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Height = 51mm Width = 23mm Depth = 21mm All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 15 October 2018 09:54 E8	Earth Terminal Capacity 1	6 x 1mm2		
Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1 Module Size All products listed conform to current British or European standard and the product information is correct at the time of going to press. BIllustrations and diagrams are reproduced within the limitations of reproduction and printing Earth Terminal Capacity 4 2 x 4mm2 Multi-strand 1 x 6mm2 Face plate must be earthed -5° to +40°C Recommended Location Internal Use Only 2000m BS EN 60669-1 Height = 51mm Width = 23mm Depth = 21mm All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 15 October 2018 09:54 E8	Earth Terminal Capacity 2	5 x 1.5mm2		
Earth Terminal Capacity 5 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Module Size All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:54	Earth Terminal Capacity 3			
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Module Size Height = 51mm Width = 23mm Depth = 21mm All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Torrect as at 15 October 2018 09:54 E8	Earth Terminal Capacity 4	2 x 4mm2 Multi-strand		
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Module Size Height = 51mm Width = 23mm Depth = 21mm All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing To treet at 15 October 2018 09:54 test	Earth Terminal Capacity 5			
Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Module Size Height = 51mm Width = 23mm Depth = 21mm All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing To treet at 15 October 2018 09:54 E8				
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Module Size Height = 51mm Width = 23mm Depth = 21mm All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:54		·		
Maximum Installation Altitude Standard/Approval BS EN 60669-1 Module Size Height = 51mm Width = 23mm Depth = 21mm All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:54				
Module Size Height = 51mm Width = 23mm Depth = 21mm All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:54	Maximum Installation Altitude	2000m		
Module Size Height = 51mm Width = 23mm Depth = 21mm All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 15 October 2018 09:54 E8	Standard/Approval	BS EN 60669-1		
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of		Height = 51mm Width = 23mm Depth = 21mm		
the limitations of reproduction and printing guarantee an exact colour match and shadings of E8	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
process and are not binding. of certain finishes. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ	the limitations of reproduction and printing process and are not binding.	guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:54 AM E&OE	

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









