Hamilton

making connections beautifully

| Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio | | |
|---|---|--|
| IR212AB-B | | |
| | | |
| Item Image | Wiring | Dimensions |
| | Image: second | |
| Primary Range | GRID-IT | |
| Insert Type | 20AX 2 Way Rocker Module | |
| Plate Finish | GRID-IT Module No Plate Colour | |
| Insert Colour | Antique Brass/Black | |
| EAN13 Barcode | 5051164019617 | |
| Weight | 35 GR | |
| Switched Poles | Single | |
| Current Rating | 20AX | |
| Voltage | 20/AA 220/250V AC | |
| Maximum Load | 20 Amp inductive | |
| | 20 Amp inductive 50Hz | |
| Mains Frequency IP Rating | IP2XD | |
| | | |
| Contact Gap Minimum | 3mm 5 x 1mm2 | |
| Terminal Capacity 1 | 4 x 1.5mm2 | |
| Terminal Capacity 2 | 4 x 1.5mm2 2 x 2.5mm2 | |
| Terminal Capacity 3 | | |
| Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| Terminal Capacity 5 | 1 x 6mm2 | |
| Earth Terminal Capacity 1 | 6 x 1mm2 | |
| Earth Terminal Capacity 2 | 5 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Face plate must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS EN 60669-1 | |
| Module Size | Height = 51mm Width = 23mm Depth = 21mm | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 15 October 2018 09:55 AM E&OE |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Ro T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Of E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in | ad, Brislington, Bristol, BS4 5NZ fice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84 | Listed in Strimble LUCKINS Product selector CSFPus (50) CSSFPus (50) C |

SL