Hamilton

making connections beautifully

| | Wiring Accessories • Circuit Protection • Sm | art Lighting Control & Multi-room Audio |
|--|---|--|
| | IR212BC-B | |
| Grid-IT 20AX 2 Way Rocker Module Bright Chrome/Black | | |
| | | |
| | Image: second | |
| Primary Range | GRID-IT | |
| Insert Type | 20AX 2 Way Rocker Module | |
| Plate Finish | GRID-IT Module No Plate Colour | |
| Insert Colour | Bright Chrome/Black | |
| EAN13 Barcode | 5051164029616 | |
| Weight | 43 GR | |
| Switched Poles | Single | |
| Current Rating | 20AX | |
| Voltage | 220/250V AC | |
| Maximum Load | 20 Amp inductive | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | 3mm | |
| Terminal Capacity 1 | 5 x 1mm2 | |
| Terminal Capacity 2 | 4 x 1.5mm2 | |
| | 2 x 2.5mm2 | |
| Terminal Capacity 3 | | |
| Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| Terminal Capacity 5 | 1 x 6mm2 | |
| Earth Terminal Capacity 1 | 6 x 1mm2 | |
| Earth Terminal Capacity 2 | 5 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Face plate must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS EN 60669-1 | |
| Module Size All products listed conform to current British or European standard and the product information is correct at the time of going to press. | Height = 51mm Width = 23mm Depth = 21mm All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 15 October 2018 09:55 AM E&OE |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville F T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com Registered i | Road, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB n London No. 941624 VAT Registration No. 222 6607 84 | Listed in STrimble Product Posterior Cast No. 14/12/2007 |

SL