SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

IRR2WSS-B

Grid-IT 10AX Retractive 2 Way and Off Rocker Module Satin Steel/Black

| | | 0 | |
|---|---|---|---|
| | 1 | | |
| | | | |
| | | | K |
| 4 | | | |

Item Image



BS EN 60669



Dimensions

| G | L2 L1 | | | |
|---|---|---|--|--|
| Primary Range | GRID-IT | | | |
| Insert Type | 10AX Retractive 2 Way + Off Rocker Module | | | |
| Plate Finish | GRID-IT Module No Plate Colour | | | |
| Insert Colour | Satin Steel/Black | | | |
| EAN13 Barcode | 5051164139650 | | | |
| Weight | 34 GR | | | |
| Switched Poles | Single | | | |
| Current Rating | 10AX | | | |
| Voltage | 220/250V AC | | | |
| Maximum Load | 10 Amp inductive | | | |
| Mains Frequency | 50Hz | | | |
| IP Rating | IP2XD | | | |
| Contact Gap Minimum | 3mm | | | |
| Terminal Capacity 1 | 5 x 1mm2 | | | |
| Terminal Capacity 2 | 4 x 1.5mm2 | | | |
| Terminal Capacity 3 | 1 x 2.5mm2 | | | |
| Terminal Capacity 4 | 1 x 4mm2 Multi-strand | | | |
| Terminal Capacity 5 | 1 x 6mm2 | | | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | | | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | | | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | | | |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand | | | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | | | |
| Product Class 1 | Face plate must be earthed | | | |
| Ambient Operating Temperature | -5° to +40°C | | | |
| Recommended Location | Internal Use Only | | | |
| Maximum Installation Altitude | 2000m | | | |
| Standard/Approval | BS EN 60669-1 | | | |
| Module Size | Height = 51mm Width = 23mm Depth = 21mm | | | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. | | |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 15 October 2018 09:55 AM E&OE | | |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









