



## IRRTSC-B

### Grid-IT 10AX Push To Make/Push to Break Retractive Rocker Module Satin Chrome/Black

| Item Image  | Wiring  | Dimensions  |
|---|---|---|
|    |                              |   |
| Primary Range   | GRID-IT   |   |
| Insert Type   | 10AX Push To Make/Break Retractive Rocker Module  |   |
| Plate Finish  | GRID-IT Module No Plate Colour  |   |
| Insert Colour   | Satin Chrome/Black  |   |
| EAN13 Barcode   | 5051164119737   |   |
| Switched Poles  | Single  |   |
| Current Rating  | 10AX  |   |
| Voltage   | 220/250V AC   |   |
| Maximum Load  | 10 Amp inductive  |   |
| Mains Frequency   | 50Hz  |   |
| IP Rating   | IP2XD   |   |
| Contact Gap Minimum   | 3mm   |   |
| Terminal Capacity 1   | 5 x 1mm <sup>2</sup>  |   |
| Terminal Capacity 2   | 4 x 1.5mm <sup>2</sup>  |   |
| Terminal Capacity 3   | 1 x 2.5mm <sup>2</sup>  |   |
| Terminal Capacity 4   | 1 x 4mm <sup>2</sup> Multi-strand   |   |
| Terminal Capacity 5   | 1 x 6mm <sup>2</sup>  |   |
| Earth Terminal Capacity 1   | 5 x 1mm <sup>2</sup>  |   |
| Earth Terminal Capacity 2   | 4 x 1.5mm <sup>2</sup>  |   |
| Earth Terminal Capacity 3   | 3 x 2.5mm <sup>2</sup>  |   |
| Earth Terminal Capacity 4   | 1 x 4mm <sup>2</sup> Multi-strand   |   |
| Earth Terminal Capacity 5   | 1 x 6mm <sup>2</sup>  |   |
| Product Class 1   | Face plate must be earthed  |   |
| Ambient Operating Temperature   | -5° to +40°C  |   |
| Recommended Location  | Internal Use Only   |   |
| Maximum Installation Altitude   | 2000m   |   |
| Standard/Approval   | BS EN 60669-1   |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.         | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 15 October 2018 09:55 AM E&OE   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
 T: +44 (0)1747 860088 F: +44 (0)1179 710414  
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
 Registered in London No. 941624 VAT Registration No. 222 6607 84

