Hamilton

making connections beautifully

	Wiring Accessories • Circuit Protection • Sm	nart Lighting Control & Multi-room Audio
	ISS2SS-W	
Grid-IT 2 gan	g 13A Double Pole Switched Socket Module S	atin Steel/White
<u> </u>		
Item Image	Wiring	Dimensions
	DUBLE POLE	
Primary Range	GRID-IT	
Insert Type	2 gang 13A Double Pole Switched Socket Module	
Plate Finish	GRID-IT Module No Plate Colour	
Insert Colour	Satin Steel/White	
EAN13 Barcode	5051164149222	
Switched Poles	Double	
Current Rating	13 Amp	
Voltage	220/250V AC	
Maximum Load	13 Amp	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	4 x 2.5mm2	
Terminal Capacity 2	3 x 4mm2	
Terminal Capacity 3	2 x 6mm2 Multi-Strand	
Terminal Capacity 4	1 x 10mm2	
Earth Terminal Capacity 1	4 x 2.5mm2	
Earth Terminal Capacity 2	3 x 4mm2	
Earth Terminal Capacity 3	2 x 6mm2 Multi-strand	
Earth Terminal Capacity 4	1 x 10mm2	
Product Class 1	Face plate must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS 1363-2	
Additional Notes	Dual Earth: Yes	
Module Size	Height = 64mm Width = 128mm Depth = 28mm	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:55 Al E&O

E: info@hamilton-litestat.com www.hamilton-litestat.com



SL