SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

KP3X40

KP3X40 White Plastic 3x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmers max 300w per gang White		
Item Image	Wiring	Dimensions
	Dimmer Wiring Lee No prod Lamp Note: When charge as a De Winy Server that on deal Nation When charge as A De Winy Server that on deal Nation When and shall be an another any police as two yell from one of the server that one of one deeme per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross of the seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross off to seal or only one deem per cross of the seal or only one deem per cross of the seal or only one deem per cross of the seal or only one deem per cross of the seal or only one deem per cross of the seal or only one deem per cross of the seal or only one deem per cross of the seal or only one deem per cross of the seal or only one deem per cross of the seal or only one deem per cross of the seal or only one deem per cross of the seal or only one deem per cross of the seal or only one deem per cross of the seal or only one deem per cross of the seal or only one deem per cross of the seal or only one deem per cross of the seal or only one deem per cross of the seal or only one deem per cross of the seal or only one deem per cross of the seal or only one deem per cro	
Primary Range	White Plastic 3 gang 400w Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer max 300W per gang	
Insert Type		
Plate Finish	White Plastic White White	
Insert Colour		
EAN13 Barcode	5017503119684	
Dimensions (Nominal)	Double: Height = 86.0mm Width = 146.0mm Depth = 8.5mm	
Weight	237 GR	
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = N/A	
Minimum Wall Box Depth	35mm	
Wattage	300W per gang	
Switched Poles	Single	
Current Rating	1.25 Amps per gang	
Voltage	220/250V AC	
Maximum Load	300W resistive per gang	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	N/A	
Terminal Capacity 1	2 x 1mm2	
Terminal Capacity 2	2 x 1.5mm2	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Face plate must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-2-1	
Additional Notes	Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 03:54 PM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









