Hamilton

making connections beautifully

SL

	Wiring Accessories • Circuit Protection • Sm	nart Lighting Control & Multi-room Audio						
LD1X40SB-SB								
Linea-Duo CFX Satin Brass Frame/Satin Brass Front 1x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Satin Brass								
Item Image	Wiring	Dimensions						
	Director Writing The formation Part of the Director of the Corp Chat Tree Way Beakching Unit of the Corp Chat T	ELINEALUS CFX VAU Besistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer						
Primary Range	Linea-Duo CFX							
Insert Type	1 gang 400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer							
Plate Finish	Linea-Duo CFX Satin Brass Frame/Satin Brass							
Insert Colour	Satin Brass							
EAN13 Barcode	5017504159412							
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm							
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips							
Minimum Wall Box Depth	35mm							
Wattage	400W							
Switched Poles	Single							
Current Rating	1.66 Amp							
Voltage	220/250V AC							
Maximum Load	400W resistive Min Load							
Mains Frequency	50Hz							
IP Rating	IP2XD							
Contact Gap Minimum	N/A							
Terminal Capacity 1	2 x 1mm2							
Terminal Capacity 2	2 x 1.5mm2							
Earth Terminal Capacity 1	5 x 1mm2							
Earth Terminal Capacity 2	4 x 1.5mm2							
Earth Terminal Capacity 3	3 x 2.5mm2							
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand							
Earth Terminal Capacity 5	1 x 6mm2							
Product Class 1	Face plate must be earthed							
Ambient Operating Temperature	-5° to +40°C							
Recommended Location	Internal Use Only							
Maximum Installation Altitude	2000m							
Standard/Approval	BS EN 60669-2-1							
Additional Notes	Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.							

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LD1X40SB-SB

Linea-Duo CFX Satin Brass Frame/Satin Brass Front 1x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Satin Brass

	Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174			
	All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.		It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
	Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	nd printing guarantee an exact colour match and shadings of		Correct as at 15 October 2018 08:13 AM E&OE	
		d, Brislington, Bristol, BS4 5NZ ce 1 Rushmills, Bedford Road, Northampton NN4 7YB ondon No. 941624 VAT Registration No. 222 6607 84		Listed in STrim	ble. riba product selector n55Plus bs. 150 1900 1 Stagement

SL