Hamilto

making connections beautifully

SL Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio LD1X60RB-RB Linea-Duo CFX Richmond Bronze Frame/Richmond Bronze Front 1 gang 600W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Richmond Bronze Item Image Wiring Dimensions Hamilton LINEA DOL OL A 1X60 Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer E DE \bigcirc Linea-Duo CFX Primary Range Insert Type 1 gang 600W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Plate Finish Linea-Duo CFX Richmond Bronze Frame/Richmond Bronze Insert Colour **Richmond Bronze** 5017504035556 EAN13 Barcode Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Box Fixing = 60.3mm Grid Fixing = CFX Clips **Fixing Hole Centres** Minimum Wall Box Depth 35mm Wattage 600W Switched Poles Single Current Rating 2.5 Amp Voltage 220/250V AC 600W resistive Min Load 100W Maximum Load Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum N/A Terminal Capacity 1 2 x 1mm2 **Terminal Capacity 2** 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Internal Use Only **Recommended Location** Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltage halogen lamps- dimmers Additional Notes should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LD1X60RB-RB

Linea-Duo CFX Richmond Bronze Frame/Richmond Bronze Front 1 gang 600W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Richmond Bronze

	· ·	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 08:13 AN E&OI
	ad, Brislington, Bristol, BS4 5NZ lice 1 Rushmills, Bedford Road, Northampton NN4 7YB ondon No. 941624 VAT Registration No. 222 6607 84	Listed in Trimble. LUCKINS riba product selector

SL