




LD2J45SN-BSB

Linea-Duo CFX Satin Nickel Frame/Bright Steel Front 2 gang RJ45 CAT 5E Outlet - Unshielded Black

Item Image	Wiring	Dimensions																											
	 <p>RJ45 CAT5e and CAT6 Wiring Colour Codes</p> <table border="1" data-bbox="803 583 966 674"> <thead> <tr> <th>Pin</th> <th>EIA Wiring Schedule (T568A)</th> <th>ISO/IEC 11801 (T568B)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>WHITE / Green</td> <td>WHITE / Orange</td> </tr> <tr> <td>2</td> <td>GREEN / White</td> <td>ORANGE / Green</td> </tr> <tr> <td>3</td> <td>WHITE / Orange</td> <td>BLUE / White</td> </tr> <tr> <td>4</td> <td>BLUE / White</td> <td>WHITE / Blue</td> </tr> <tr> <td>5</td> <td>WHITE / Blue</td> <td>WHITE / Orange</td> </tr> <tr> <td>6</td> <td>ORANGE / White</td> <td>WHITE / Brown</td> </tr> <tr> <td>7</td> <td>WHITE / Brown</td> <td>BROWN / White</td> </tr> <tr> <td>8</td> <td>BROWN / White</td> <td>BROWN / Brown</td> </tr> </tbody> </table> <p>Please always check with the colour coding found on the product.</p>	Pin	EIA Wiring Schedule (T568A)	ISO/IEC 11801 (T568B)	1	WHITE / Green	WHITE / Orange	2	GREEN / White	ORANGE / Green	3	WHITE / Orange	BLUE / White	4	BLUE / White	WHITE / Blue	5	WHITE / Blue	WHITE / Orange	6	ORANGE / White	WHITE / Brown	7	WHITE / Brown	BROWN / White	8	BROWN / White	BROWN / Brown	 <p>Hamilton® LINEA DUO CFX 2J45 2 gang RJ45 - CAT 5E Outlet Unshielded 8 wire</p>
Pin	EIA Wiring Schedule (T568A)	ISO/IEC 11801 (T568B)																											
1	WHITE / Green	WHITE / Orange																											
2	GREEN / White	ORANGE / Green																											
3	WHITE / Orange	BLUE / White																											
4	BLUE / White	WHITE / Blue																											
5	WHITE / Blue	WHITE / Orange																											
6	ORANGE / White	WHITE / Brown																											
7	WHITE / Brown	BROWN / White																											
8	BROWN / White	BROWN / Brown																											

Primary Range	Linea-Duo CFX
Insert Type	2 gang RJ45 CAT 5E Outlet - Unshielded
Plate Finish	Linea-Duo CFX Satin Nickel Frame/Bright Steel
Insert Colour	Black
EAN13 Barcode	5017504301583
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	N/A
IP Rating	IP2XD
Contact Gap Minimum	N/A
Earth Terminal Capacity 1	5 x 1mm ²
Earth Terminal Capacity 2	4 x 1.5mm ²
Earth Terminal Capacity 3	3 x 2.5mm ²
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand
Earth Terminal Capacity 5	1 x 6mm ²
Product Class 1	Must be earthed (ref BS7671 415.2.1)
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
EuroFix Additional Notes	Can be used in both EIA 568A and EIA 568B wiring schedules
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174

<p>All products listed conform to current British or European standard and the product information is correct at the time of going to press.</p>	<p>All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.</p>	<p>It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p>
<p>Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.</p>	<p>Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.</p>	<p>Correct as at 15 October 2018 08:14 AM E&OE</p>

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
 T: +44 (0)1747 860088 F: +44 (0)1179 710414
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
 Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM1238