## Hamilton

## making connections beautifully

SL

|  |  | -  |  |  |
|--|--|--|--|--|
| Wining Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio  |  |  |  |  |
| LD2X40PB-AB  |  |  |  |  |
| Linea-Duo CFX Polished Brass Frame/Antique Brass Front 2x400W Resistive Leading Edge Push On-Off Rotary 2 Way<br>Switching Dimmers max 300W per gang Polished Brass  |  |  |  |  |
| Item Image   | Wiring   | Dimensions   |  |  |
|  | Dromer Weing<br>Weing and a state of the state | ELIDEA DUO CFX<br>2x0<br>Besistive Leading Edge Push On-Off Rotary<br>2 Way Switching Dimmer |  |  |
| Primary Range  | Linea-Duo CFX  |  |  |  |
| Insert Type  | 2 gang 400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer max 300W per gang   |  |  |  |
| Plate Finish   | Linea-Duo CFX Polished Brass Frame/Antique Brass   |  |  |  |
| Insert Colour  | Polished Brass   |  |  |  |
| EAN13 Barcode  | 5017504129422  |  |  |  |
| Dimensions (Nominal)   | Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm   |  |  |  |
| Fixing Hole Centres  | Box Fixing = 60.3mm Grid Fixing = CFX Clips  |  |  |  |
| Minimum Wall Box Depth   | 35mm   |  |  |  |
| Wattage  | 300W per gang  |  |  |  |
| Switched Poles   | Single   |  |  |  |
| Current Rating   | 1.25 Amps per gang   |  |  |  |
| Voltage  | 220/250V AC  |  |  |  |
| Maximum Load   | 300W resistive per gang  |  |  |  |
| Mains Frequency  | 50Hz   |  |  |  |
| IP Rating  | IP2XD  |  |  |  |
| Contact Gap Minimum  | N/A  |  |  |  |
| Terminal Capacity 1  | 2 x 1mm2   |  |  |  |
| Terminal Capacity 2  | 2 x 1.5mm2   |  |  |  |
| Earth Terminal Capacity 1  | 5 x 1mm2   |  |  |  |
| Earth Terminal Capacity 2  | 4 x 1.5mm2   | 4 x 1.5mm2   |  |  |
| Earth Terminal Capacity 3  | 3 x 2.5mm2   |  |  |  |
| Earth Terminal Capacity 4  | 1 x 4mm2 Multi-strand  |  |  |  |
| Earth Terminal Capacity 5  | 1 x 6mm2   |  |  |  |
| Product Class 1  | Face plate must be earthed   |  |  |  |
| Ambient Operating Temperature  | 5° to +40°C  |  |  |  |
| Recommended Location   | Internal Use Only  |  |  |  |
| Maximum Installation Altitude  | 2000m  |  |  |  |
| Standard/Approval  | BS EN 60669-2-1  |  |  |  |
| ditional Notes Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. |  |  |  |  |

# Hamilton

## making connections beautifully

#### Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

### LD2X40PB-AB

### Linea-Duo CFX Polished Brass Frame/Antique Brass Front 2x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmers max 300W per gang Polished Brass

|   | 5 1 5 5  |  |
|---|--|--|
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665<br>CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B<br>Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited<br>BS EN ISO 9001 : 2015 Quality Management System.   | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within<br>the limitations of reproduction and printing<br>process and are not binding.                | Due to manufacturing processes we cannot<br>guarantee an exact colour match and shadings of<br>of certain finishes.  | Correct as at 15 October 2018 08:14 AM<br>E&OE   |
|   | ad, Brislington, Bristol, BS4 5NZ<br>fice 1 Rushmills, Bedford Road, Northampton NN4 7YB<br>London No. 941624 VAT Registration No. 222 6607 84   | Listed in STrimble product selector CER Re. FM1238   |

SL