



## LD2XLEDITB100BC-BK

Linea-Duo CFX Bright Chrome Frame/Black Nickel 2g 100W LED 2 Way Push On/Off Rotary Dimmer Bright Chrome

Item Image	Wiring	Dimensions
		
Primary Range	Linea-Duo CFX	
Insert Type	2 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer	
Plate Finish	Linea-Duo CFX Bright Chrome Frame/Black Nickel	
Insert Colour	Bright Chrome	
EAN13 Barcode	5017504082529	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Wattage	5-70W Per Gang	
Switched Poles	Single	
Current Rating	0.3A Per Gang	
Voltage	230V-240V	
Maximum Load	5-70W Per Gang	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Terminal Capacity 1	2X1mm <sup>2</sup>	
Terminal Capacity 2	2X1.5mm <sup>2</sup>	
Earth Terminal Capacity 1	5X1mm <sup>2</sup>	
Earth Terminal Capacity 2	4X1.5mm <sup>2</sup>	
Earth Terminal Capacity 3	3X2.5mm <sup>2</sup>	
Earth Terminal Capacity 4	1X4mm <sup>2</sup> Multi-Strand	
Earth Terminal Capacity 5	1X6mm <sup>2</sup>	
Product Class 1	Face plate must be earthed	
Ambient Operating Temperature	-5°C to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-2-1	
Additional Notes	Trailing Edge & Leading Edge Dimmer	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 08:14 AM E&OE