

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LD2XLEDITB100HB-HB

Linea-Duo CFX Connaught Bronze Frame/Connaught Bronze 2g 100W LED 2 Way Push On/Off Rotary Dimmer Connaught Bronze

Primary Range Linea-Duo CFX Insert Type 2 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Plate Finish Linea-Duo CFX Connaught Bronze Frame/Connaught Bronze EAN13 Barcode 5017504082628 Dimensions (Nominal) 51ngle: Highlet 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz Linea-Duo CFX Linea-Duo Linea-Duo CFX Linea-Duo Lin	con
Primary Range Linea-Duo CFX Insert Type 2 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Plate Finish Linea-Duo CFX Connaught Bronze Frame/Connaught Bronze Insert Colour Connaught Bronze Frame/Connaught Bronze EAN13 Barcode 5017504082628 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Switched Poles Single Current Rating 0.3A Per Gang Mains Frequency 50Hz IP Rating 1P2XD Terminal Capacity 1 2X11mm² Terminal Capacity 1 2X11mm² Terminal Capacity 1 5X11mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X44mm² Multi-Strand	
Primary Range Linea-Duo CFX Insert Type 2 gang 100W LED Trailling/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Plate Finish Linea-Duo CFX Connaught Bronze Insert Colour Connaught Bronze EAN13 Barcode 5017504082628 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Minimum Maximum Load 5-	19.3
Insert Type 2 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Plate Finish Linea-Duo CFX Connaught Bronze Frame/Connaught Bronze Insert Colour Connaught Bronze EAN13 Barcode 5017504082628 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 1 2X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand Earth Iterminal Capacity 4 INAMP Multi-Strand	
Plate Finish Linea-Duo CFX Connaught Bronze Frame/Connaught Bronze Insert Colour Connaught Bronze EAN13 Barcode 5017504082628 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load Maris Frequency Folkz IP Rating IP2XD Terminal Capacity 1 2x1mm² Terminal Capacity 2 2x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand	
Insert Colour Connaught Bronze EAN13 Barcode 5017504082628 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand	
EAN13 Barcode 5017504082628 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1nm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand	
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 Earth Terminal Capacity 1 Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand	
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1X4mm² Multi-Strand	
Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2x1.5mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand	
Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand	
Switched Poles Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 1P Rating 1P2XD Terminal Capacity 1 2x1mm² Terminal Capacity 2 2x1.5mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-Strand	
Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand	
Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand	
Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand	
Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand	
IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand	
Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand	
Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand	
Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand	
Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand	
Earth Terminal Capacity 3 3X2.5mm ² Earth Terminal Capacity 4 1X4mm ² Multi-Strand	
Earth Terminal Capacity 4 1X4mm² Multi-Strand	
Earth Terminal Capacity 5 1X6mm²	
Product Class 1 Face plate muct be earthed	
Ambient Operating Temperature -5°C to +40°C	
Recommended Location Internal Use Only	
Maximum Installation Altitude 2000m	
Standard/Approval BS EN 60669-2-1	
Additional Notes Trailing Edge & Leading Edge Dimmer	
Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174	
All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the ri and dimensions withou	
Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. Correct as guarantee an exact colour match and shadings of of certain finishes.	ight to alter designs

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)17179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio