## Hamilton

## making connections beautifully

SL

| Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio   |  |  |  |
|---|--|--|--|
| LD2XTMRB-RBB  |  |  |  |
| Linea-Duo CFX Richmond Bronze Frame/Richmond Bronze Front 2x250W/210VA Resistive/Inductive Trailing Edge Touch<br>Master Multi-Way Dimmers Black Nickel/Black |  |  |  |
| Item Image  | Wiring   | Dimensions   |  |
|   | Multi- Way Wiring using Slave module(s)  | Electronic Construction of the formula of the formu |  |
| Primary Range   | Linea-Duo CFX  |  |  |
| Insert Type   | 2 gang 250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmer  |  |  |
| Plate Finish  | Linea-Duo CFX Richmond Bronze Frame/Richmond Bronze  |  |  |
| Insert Colour   | Black Nickel/Black   |  |  |
| EAN13 Barcode   | 5017504035969  |  |  |
| Dimensions (Nominal)  | Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm   |  |  |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips  |  |  |
| Minimum Wall Box Depth  | 35mm   |  |  |
| Wattage   | 250W Resistive 210VA Inductive   |  |  |
| Switched Poles  | N/A  |  |  |
| Current Rating  | 1.1 Amps per gang  |  |  |
| Voltage   | 220/250V AC  |  |  |
| Maximum Load  | 250W Resistive per gang 210VA Inductive Min Load 25W/25VA  |  |  |
| Mains Frequency   | 50Hz   |  |  |
| IP Rating   | IP2XD  |  |  |
| Contact Gap Minimum   | N/A  |  |  |
| Terminal Capacity 1   | 2 x 1mm2   |  |  |
| Terminal Capacity 2   | 2 x 1.5mm2   |  |  |
| Earth Terminal Capacity 1   | 5 x 1mm2   |  |  |
| Earth Terminal Capacity 2   | 4 x 1.5mm2   |  |  |
| Earth Terminal Capacity 3   | 3 x 2.5mm2   |  |  |
| Earth Terminal Capacity 4   | 1 x 4mm2 Multi-strand  |  |  |
| Earth Terminal Capacity 5   | 1 x 6mm2   |  |  |
| Product Class 1   | Face plate must be earthed   |  |  |
| Ambient Operating Temperature   | -5° to +40°C   |  |  |
| Recommended Location  | Internal Use Only  |  |  |
| Maximum Installation Altitude   | 2000m  |  |  |
| Standard/Approval Additional Notes  | BS EN 60669-2-1<br>TRAILING EDGE TECHNOLOGY DIMMERS. Are suitable for control of both resistive and inductive loads. When used for<br>dimming low voltage electronic halogen transformers it must be noted that the dimmer controls the primary side of the<br>transformer. Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps-<br>dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for<br>compatibility. When using mains voltage halogen load transformer - maximum rating is 210VA. NOTE: For multi-way<br>switching a push to make retractive switch should be installed in the other positions. (Note:standard two way switches will<br>not work with this product) |  |  |

# Hamilton

## making connections beautifully

#### Wining Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

### LD2XTMRB-RBB

#### Linea-Duo CFX Richmond Bronze Frame/Richmond Bronze Front 2x250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmers Black Nickel/Black

| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665<br>CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B<br>Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 |  |
|---|--|--|
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited<br>BS EN ISO 9001 : 2015 Quality Management System.   | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within<br>the limitations of reproduction and printing<br>process and are not binding.                | Due to manufacturing processes we cannot<br>guarantee an exact colour match and shadings of<br>of certain finishes.  | Correct as at 15 October 2018 08:14 AM<br>E&OE   |
|   | ad, Brislington, Bristol, BS4 5NZ<br>ice 1 Rushmills, Bedford Road, Northampton NN4 7YB<br>ondon No. 941624 VAT Registration No. 222 6607 84   | Listed in Trimble Doduct Product Selector DSSPlus  |

SL