Hamilto

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LD3XLEDITB100RB-RB

Linea-Duo CFX Richmond Bronze Frame/Richmond Bronze 3g 100W LED 2 Way Push On/Off Rotary Dimmer Richmond

Bronze Item Image Wiring Dimensions Hamilton LINEA DUO C 3XLEDITB LEDITB100 2 Way Dimme Linea-Duo CEX Primary Range Insert Type 3 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Plate Finish Linea-Duo CFX Richmond Bronze Frame/Richmond Bronze Insert Colour **Richmond Bronze** 5017504082956 EAN13 Barcode Dimensions (Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm Box Fixing = 120.6mm Grid Fixing = CFX Clips **Fixing Hole Centres** Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang 230V-240V Voltage Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD **Terminal Capacity 1** 2X1mm² Terminal Capacity 2 2X1 5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand Earth Terminal Capacity 5 1X6mm² Product Class 1 Face plate muct be earthed Ambient Operating Temperature -5°C to +40°C Internal Use Only Recommended Location 2000m Maximum Installation Altitude Standard/Approval BS EN 60669-2-1 Additional Notes Trailing Edge & Leading Edge Dimmer Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Patents and Trademarks Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All accessories are manufactured under an accredited It is the policy of the company to improve products All products listed conform to current British or BS EN ISO 9001 : 2015 Quality Management System. as part of our development programme. European standard and the product information is Therefore, we reserve the right to alter designs and dimensions without prior notice. correct at the time of going to press. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 15 October 2018 08:15 AM E&OE the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding of certain finishes. Listed in STrim

SECA

LUCKINS

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YE Registered in London No. 941624 VAT Registration No. 222 6607 84

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio