Hamilton

making connections beautifully

TRAILING EDGE TECHNOLOGY DIMMERS. Are suitable for control of both resistive and inductive loads. When used for dimming low voltage electronic halogen transformers it must be noted that the dimmer controls the primary side of the transformer. Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps-dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for

compatibility. When using mains voltage halogen load transformer - maximum rating is 210VA. NOTE: For multi-way switching a push to make retractive switch should be installed in the other positions. (Note:standard two way switches will

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio LD3XTMEB-EBB Linea-Duo CFX Etrium Bronze Frame/Etrium Bronze Front 3x250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmers Etrium Bronze/Black Item Image Wiring Dimensions Hamilton LINEA DUO GFA 3XTM Resistive/Inductive Trailing Edge Touch Master Multi- Way Wiring using Slave module(s) Linea-Duo CFX Primary Range Insert Type 3 gang 250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmer Plate Finish Linea-Duo CFX Etrium Bronze Frame/Etrium Bronze Insert Colour Etrium Bronze/Black EAN13 Barcode 5017504036164 Dimensions (Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm Box Fixing = 120.6mm Grid Fixing = CFX Clips **Fixing Hole Centres** Minimum Wall Box Depth 35mm Wattage 250W Resistive 210VA Inductive Switched Poles N/A Current Rating 1.1 Amps per gang Voltage 220/250V AC Maximum Load 250W Resistive per gang 210VA Inductive Min Load 25W/25VA Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum N/A Terminal Capacity 1 2 x 1mm2 **Terminal Capacity 2** 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2

Face plate must be earthed

not work with this product)

-5° to +40°C Internal Use Only

BS EN 60669-2-1

2000m

SL

Product Class 1

Ambient Operating Temperature

Recommended Location Maximum Installation Altitude

Standard/Approval

Additional Notes

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LD3XTMEB-EBB

Linea-Duo CFX Etrium Bronze Frame/Etrium Bronze Front 3x250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmers Etrium Bronze/Black

	•	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 08:15 A E&C
	fice 1 Rushmills, Bedford Road, Northampton NN4 7YB	Listed in STrimble Product OSSPIUS

SL