Hamilton

making connections beautifully

SL

| Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio | | |
|--|--|--|
| LD45SS1SN-SSW | | |
| Linea-Duo CFX Satin Nickel Frame/Satin Steel Front 45A Double Pole Rocker + Neon + 13A Switched Socket Red+Satin Steel/White | | |
| Item Image | Wiring | Dimensions |
| | | |
| | | Hemilton LINE AUDO CRX 45531 Double Pole Red Rocker & Neon & 13A Switched Socket |
| | | |
| Primary Range | Linea-Duo CFX | |
| Insert Type | 45A Double Pole Red Rocker + Neon + 13A Switched Socket | |
| Plate Finish | Linea-Duo CFX Satin Nickel Frame/Satin Steel | |
| Insert Colour | Red+Satin Steel/White | |
| EAN13 Barcode | 5017504227708 | |
| Dimensions (Nominal) | Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm | |
| Fixing Hole Centres | Box Fixing = 120.6mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | Double | |
| Current Rating | Switch 45 Amp Socket 13 Amp 220/250V AC | |
| Voltage Maximum Load | Switch 45 Amp Socket 13 | |
| | 50Hz | |
| Mains Frequency IP Rating | IP2XD | |
| Contact Gap Minimum | 3mm | |
| Terminal Capacity 1 | 3 x 6mm2 | |
| Terminal Capacity 2 | 2 x 10mm2 | |
| Terminal Capacity 3 | 1 x 16mm2 | |
| Earth Terminal Capacity 1 | 3 x 6mm2 | |
| Earth Terminal Capacity 2 | 2 x 10mm2 | |
| Earth Terminal Capacity 3 | 1 x 16mm2 | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS 4177 | |
| Patents and Trademarks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 15 October 2018 08:15 AM E&OE |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com www.hamilton-litestat. | | |