## Hamilton

## making connections beautifully

SL

	<u> </u>	etter te becautiany				
	Wiring Accessories	mart Lighting Control & Multi-room Audio				
	LD4X40AB-AB					
	/Antique Brass Front 4x400W Resistive Lea ching Dimmers max 300W per gang Antique					
Item Image	Wiring	Dimensions				
	Dimmer Weing Loop In Loop O.G. Two Way Subtring   Weing Weing   Weing Weing   Big	LINEA DUO CFX 4X0 Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer				
Primary Range	Linea-Duo CFX					
Insert Type	4 gang 400W Resistive Leading Edge Push On-Off Rotary 2	Way Switching Dimmer max 300W per gang				
Plate Finish	Linea-Duo CFX Antique Brass Frame/Antique Brass					
Insert Colour	Antique Brass					
EAN13 Barcode	5017504189440					
Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm					
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips					
Minimum Wall Box Depth	35mm					
Wattage	300W per gang					
Switched Poles	Single					
Current Rating	1.25 Amps per gang					
Voltage	220/250V AC					
Maximum Load	300W resistive per gang					
Mains Frequency	50Hz					
IP Rating	IP2XD					
Contact Gap Minimum	N/A					
Terminal Capacity 1	2 x 1mm2					
Terminal Capacity 2	2 x 1.5mm2					
Earth Terminal Capacity 1	5 x 1mm2					
Earth Terminal Capacity 2	4 x 1.5mm2					
Earth Terminal Capacity 3	3 x 2.5mm2					
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand					
Earth Terminal Capacity 5	1 x 6mm2					
Product Class 1	Face plate must be earthed					
Ambient Operating Temperature	-5° to +40°C					
Recommended Location	Internal Use Only					
Maximum Installation Altitude	2000m					
Standard/Approval	BS EN 60669-2-1					
Additional Notes	Tungsten filament GU10 lamps must be branded with a fuse should be de-rated by 25%. When dimming LED lamps de-rated by 25%.	base. When using mains voltagehalogen lamps- dimmers ated by 75% - please contact our Technical for compatibility.				

# Hamilton

## making connections beautifully

#### Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

### LD4X40AB-AB

#### Linea-Duo CFX Antique Brass Frame/Antique Brass Front 4x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmers max 300W per gang Antique Brass

Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174				
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.		It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.		
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we canno guarantee an exact colour match and shading of certain finishes.		Correct as at 15 October 2018 08:16 AI E&O		ber 2018 08:16 AM E&OE
	d, Brislington, Bristol, BS4 5NZ ice 1 Rushmills, Bedford Road, Northampton NN4 7YB ondon No. 941624 VAT Registration No. 222 6607 84		Listed in Trimble	riba product selector	bsi. 150 9001 Quality Management

SL