Hamilton®
making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LD4XLEDITB100SB-SS
Linea-Duo CFX Satin Brass Frame/Satin Steel 4g 100W LED 2 Way Push On/Off Rotary Dimmer Satin Brass

Item Image	Wiring	Dimensions

Primary Range	Linea-Duo CFX
Insert Type	4 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer
Plate Finish	Linea-Duo CFX Satin Brass Frame/Satin Steel
Insert Colour	Satin Brass
EAN13 Barcode	5017504083205
Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Wattage	5-70W Per Gang
Switched Poles	Single
Current Rating	0.3A Per Gang
Voltage	230V-240V
Maximum Load	5-70W Per Gang
Mains Frequency	50Hz
IP Rating	IP2XD
Terminal Capacity 1	2X1mm²
Terminal Capacity 2	2X1.5mm²
Earth Terminal Capacity 1	5X1mm²
Earth Terminal Capacity 2	4X1.5mm²
Earth Terminal Capacity 3	3X2.5mm²
Earth Terminal Capacity 4	1X4mm² Multi-Strand
Earth Terminal Capacity 5	1X6mm²
Product Class 1	Face plate muct be earthed
Ambient Operating Temperature	-5°C to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS EN 60669-2-1
Additional Notes	Trailing Edge & Leading Edge Dimmer
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174

ECA COMMERCIAL ASSOCIATE   British Institute of Interior Design   Listed in Trimble LUCKINS   riba product selector   nbsPlus   bsi. ISO 9001 Quality Management CERT. No. FM11238