SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LDDENTHB-HBB

Linea-Duo CFX Connaught Bronze Frame/Connaught Bronze Front Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out (DAB Compatible) Black

Item Image	Wiring	Dimensions
	1. Undo the cable clamp screw. 2. Lift up the cover of the clamp, be carrivil not to displace the clamp are cover. 3. It is up the cover of the clamp, be carrivil not to displace the clamp of the module. 3. Insert the conductor into the terminal side which is located in the casing of the module. 4. Insert the conductor into the terminal side which is located in the casing of the module. 5. Insert the conductor into the terminal side which is located in the converted of the module security in the terminal converted on the conver	LINEA DUO CFX DENT Non-Isolated TVIFM/Satellite1/Satellite2 Quadplexer Zin/4out  86.0 50.0  MAX3 MAX3 MAX3 MAX3 MAX3 MAX3 MAX3 MAX
Primary Range	Linea-Duo CFX	
Insert Type	Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out (DAB Compatible)	
Plate Finish	Linea-Duo CFX Connaught Bronze Frame/Connaught Bronze	
Insert Colour	Black	
EAN13 Barcode	5017504038564	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	N/A	
IP Rating	IP2XD	
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
EuroFix Additional Notes	Quadplexer for use with combined TV FM and Satellite Signals (DAB compatible)	
Frequencies 1	TV=5-68 MHz 125-860 MHz	
Frequencies 2	FM=88-108 MHz	
Frequencies 3	SAT DC=950-2200 MHz	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 08:17 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











