




## LDDENTSB-SBB

### Linea-Duo CFX Satin Brass Frame/Satin Brass Front Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out (DAB Compatible) Black

| Item Image  | Wiring  | Dimensions  |
|---|---|---|
|    |  <p>1. Undo the cable clamp screw.<br/>                 2. Lift up the cover of the clamp, be careful not to displace the EMC gasket which is located on the cover.<br/>                 3. Insert the conductor into the terminal slot which is located in the casing of the module.<br/>                 4. Before closing the cover check to ensure that conductor, screening braid and cable are in the correct position as shown below.<br/>                 5. Carefully close the cover of the module ensuring that the EMC gasket is not displaced or damaged. Then tighten the cable clamp screw.</p> |  <p><b>Hamilton®</b><br/>                 LINEA DUO CFX<br/>                 DENT<br/>                 Non-Isolated TV/FM/Satellite1/Satellite2<br/>                 Quadplexer 2in/4out</p> |
| Primary Range   | Linea-Duo CFX   |   |
| Insert Type   | Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out (DAB Compatible)   |   |
| Plate Finish  | Linea-Duo CFX Satin Brass Frame/Satin Brass   |   |
| Insert Colour   | Black   |   |
| EAN13 Barcode   | 5017504151089   |   |
| Dimensions (Nominal)  | Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm  |   |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips   |   |
| Minimum Wall Box Depth  | 35mm  |   |
| Switched Poles  | N/A   |   |
| IP Rating   | IP2XD   |   |
| Contact Gap Minimum   | N/A   |   |
| Earth Terminal Capacity 1   | 5 x 1mm <sup>2</sup>  |   |
| Earth Terminal Capacity 2   | 4 x 1.5mm <sup>2</sup>  |   |
| Earth Terminal Capacity 3   | 3 x 2.5mm <sup>2</sup>  |   |
| Earth Terminal Capacity 4   | 1 x 4mm <sup>2</sup> Multi-strand   |   |
| Earth Terminal Capacity 5   | 1 x 6mm <sup>2</sup>  |   |
| Product Class 1   | Must be earthed (ref BS7671 415.2.1)  |   |
| Ambient Operating Temperature   | -5° to +40°C  |   |
| Recommended Location  | Internal Use Only   |   |
| Maximum Installation Altitude   | 2000m   |   |
| EuroFix Additional Notes  | Quadplexer for use with combined TV FM and Satellite Signals (DAB compatible)   |   |
| Frequencies 1   | TV=5-68 MHz 125-860 MHz   |   |
| Frequencies 2   | FM=88-108 MHz   |   |
| Frequencies 3   | SAT DC=950-2200 MHz   |   |
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665<br>CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B<br>Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.   | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.   |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.   | Correct as at 15 October 2018 08:17 AM E&OE   |