Hamilton

making connections beautifully

SL

SL	making conne	clions beautifully
	Wiring Accessories • Circuit Protection • Sr	nart Lighting Control & Multi-room Audio
LDDPNBK-BKB		
Linea-Duo CFX Black Nickel Frame/Black Nickel Front 1 gang 20AX Double Pole Rocker and Neon Black Nickel/Black		
Item Image	Wiring	Dimensions
	E C C C C C C C C C C C C C C C C C C C	Double Pole Rocker & Neon
Primary Range	Linea-Duo CFX	
Insert Type	1 gang 20AX Double Pole Rocker + Neon	
Plate Finish	Linea-Duo CFX Black Nickel Frame/Black Nickel	
Insert Colour	Black Nickel/Black 5017504232948	
EAN13 Barcode		
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	Double	
Current Rating	20AX	
Voltage	220/250V AC	
Maximum Load	20 Amp inductive 50Hz	
Mains Frequency	IP2XD	
IP Rating Contact Gap Minimum		
Terminal Capacity 1	3mm 3 x 2.5mm2	
Terminal Capacity 2	2 x 4mm2 Multi Strand	
Terminal Capacity 3 Earth Terminal Capacity 1	1 x 6mm2 6 x 1mm2	
	5 x 1.5mm2	
Earth Terminal Capacity 2	3 x 2.5mm2	
Earth Terminal Capacity 3 Earth Terminal Capacity 4	2 x 4mm2 Multi-strand	
	1 x 6mm2	
Earth Terminal Capacity 5	Must be earthed	
Product Class 1	-5° to +40°C	
Ambient Operating Temperature Recommended Location	-5° to +40°C	
Maximum Installation Altitude	2000m	
	BS EN 60669-1	
Standard/Approval Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 08:17 AM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1797 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com www.hamilton-litestat.com www.hamilton No. 941624 VAT Registration No. 222 6607 84		