## Hamilton

## making connections beautifully

SL

| Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio  |  |  |
|--|--|--|
| LDDSAT+PB-BSB  |  |  |
|  |  |  |
| Linea-Duo CFX Polished Brass Frame/Bright Steel Front Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out +TVF+TCS  |  |  |
| (DAB Compatible) Black   |  |  |
| Itom Imago   | Wiring   | Dimensions   |
| Item Image   | Wiring   | Dimensions   |
|  |  | Hamilton   |
|  |  |  |
|  |  | Non-Isolated TV/FM/Satellite1/Satellite2<br>Quadplexer 2in/4out + TVF + TCS  |
|  |  |  |
| SAT1 SAT2  | EVC Gesket   |  |
|  |  | 50.0   |
| TV FM/DAB  | Cable Clamp Screw J Terminal   |  |
|  | breid and cable  |  |
|  | BAT2 BAT1  |  |
|  |  |  |
|  |  |  |
|  |  |  |
| Primary Range  | Linea-Duo CFX  |  |
| Insert Type  | Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out +TVF+TCS (DAB Compatible)   |  |
| Plate Finish   | Linea-Duo CFX Polished Brass Frame/Bright Steel  |  |
| Insert Colour  | Black  |  |
| EAN13 Barcode  | 5017504131098  |  |
| Dimensions (Nominal)   | Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm  |  |
| Fixing Hole Centres  | Box Fixing = 120.6mm Grid Fixing = CFX Clips   |  |
| Minimum Wall Box Depth   | 35mm   |  |
| Switched Poles   | N/A  |  |
| IP Rating  | IP2XD  |  |
| Contact Gap Minimum  | N/A  |  |
| Earth Terminal Capacity 1  | 5 x 1mm2   |  |
| Earth Terminal Capacity 2  | 4 x 1.5mm2   |  |
| Earth Terminal Capacity 3  | 3 x 2.5mm2   |  |
| Earth Terminal Capacity 4  | 1 x 4mm2 Multi-strand  |  |
| Earth Terminal Capacity 5  | 1 x 6mm2   |  |
| Product Class 1  | Must be earthed (ref BS7671 415.2.1)   |  |
| Ambient Operating Temperature  | -5° to +40°C   |  |
| Recommended Location   | Internal Use Only  |  |
| Maximum Installation Altitude  | 2000m  |  |
| EuroFix Additional Notes   | Quadplexer for use with combined TV FM and Satellite Signals (DAB compatible) plus Telephone Slave and Female TV Socket  |  |
| Frequencies 1  | TV=5-68 MHz 125-860 MHz  |  |
| Frequencies 2  | FM=88-108 MHz  |  |
| Frequencies 3  | SAT DC=950-2200 MHz  |  |
| Frequencies 4  | TV DC=5-2200 MHz   |  |
| Patents and Trademarks   | Linea is a Registered Trade Mark No 2398665<br>CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B<br>Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press.  | All accessories are manufactured under an accredited<br>BS EN ISO 9001 : 2015 Quality Management System.   | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.   | Due to manufacturing processes we cannot<br>guarantee an exact colour match and shadings of<br>of certain finishes.  | Correct as at 15 October 2018 08:18 AM<br>E&OE   |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ<br>T: +44 (0)11747 860088 F: +44 (0)1179 710414<br>E: info@hamilton-litestat.com www.hamilton-litestat.com www.hamilton-litesta |  |  |