SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LDDTVFPB-BSW

Primary Range Linea-Duo CFX Insert Type 1 gang Non-Isolated TV (temale) Plate Finish Linea-Duo CFX Polished Brass Frame/Bright Steel Insert Colour EAN13 Barcode Dimensions Linea-Duo CFX Insert Type 1 gang Non-Isolated TV (temale) (DAB Compatible) Plate Finish Linea-Duo CFX Polished Brass Frame/Bright Steel Insert Colour EAN13 Barcode Joint South Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Milminum Wall Box Depth Jomes Sons Colour Mile South Sou	Linea-Duo CFX Polished Brass Frame/Bright Steel Front 1 gang Non-Isolated TV (female) White			
Primary Range Linea-Duo CFX Non-teoleted TV (female) Primary Range Linea-Duo CFX Insert Type 1 gang Non-Isolated TV (female) Plate Finish Linea-Duo CFX Polished Brass Frame/Bright Steel Insert Colour White EAN13 Barcode 5017504130534 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Switched Poles N/A IP Rating IP Sating IP Sati	Item Image	Wiring	Dimensions	
Primary Range Linea-Duo CFX Insert Type 1 gang Non-Isolated TV (female) (DAB Compatible) Plate Finish Linea-Duo CFX Polished Brass Frame/Bright Steel Insert Colour EAN13 Barcode Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2		Conductor Terminal Screw Correct position of conductor, screening	LINEA DUO CFX DTVF	
Insert Type 1 gang Non-Isolated TV (female) (DAB Compatible) Plate Finish Linea-Duo CFX Polished Brass Frame/Bright Steel Insert Colour White EAN13 Barcode 5017504130534 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2				
Insert Type 1 gang Non-Isolated TV (female) (DAB Compatible) Plate Finish Linea-Duo CFX Polished Brass Frame/Bright Steel Insert Colour White EAN13 Barcode 5017504130534 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2	y Range	Linea-Duo CFX		
Plate Finish Linea-Duo CFX Polished Brass Frame/Bright Steel Insert Colour White EAN13 Barcode 5017504130534 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2				
EAN13 Barcode 5017504130534 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2	Finish			
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2	Colour	<u> </u>		
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2	3 Barcode	5017504130534		
Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2	sions (Nominal)			
Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2	Hole Centres			
IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2	um Wall Box Depth	35mm		
Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2	ed Poles	N/A		
Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2	ing	IP2XD		
Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2	ct Gap Minimum	N/A		
Earth Terminal Capacity 3 3 x 2.5mm2	Ferminal Capacity 1	5 x 1mm2		
	Ferminal Capacity 2	4 x 1.5mm2		
	Ferminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 4 1 x 4mm2 Multi-strand	Ferminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 5 1 x 6mm2	Ferminal Capacity 5	1 x 6mm2		
Product Class 1 Must be earthed (ref BS7671 415.2.1)	ct Class 1	Must be earthed (ref BS7671 415.2.1)		
Ambient Operating Temperature -5° to +40°C	nt Operating Temperature	-5° to +40°C		
Recommended Location Internal Use Only	nmended Location	Internal Use Only		
Maximum Installation Altitude 2000m	um Installation Altitude	2000m		
EuroFix Additional Notes TV Outlet (IEC 169-2 Female Socket) Usually used for FM (DAB) outlet	x Additional Notes	TV Outlet (IEC 169-2 Female Socket) Usually used for FM (DAB) outlet		
Frequencies 1 TV DC=5-2200 MHz	encies 1	TV DC=5-2200 MHz		
Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174	s and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B		
All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice.	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	the limitations of reproduction and printing process and are not binding.	guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 08:18 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)1779 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered of Union No. 941624 VAT Registration No. 222 6607 84











