SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LDDTVMEB-EBB

Linea-Duo CFX Etrium Bronze Frame/Etrium Bronze Front 1 gang Non-Isolated TV (Male) Black

Primary Range  Linear-Duo CFX  Primary Range  Linear-Duo CFX	Linea-Duo CFX Etrium Bronze Frame/Etrium Bronze Front 1 gang Non-Isolated TV (Male) Black			
Insert Type  1 gang Non-Isolated TV (Male) (DAB Compatible)  Plate Finish  Linea-Duo CFX Etrium Bronze Frame/Etrium Bronze Insert Colour  Black  EAN13 Barcode  5017504039202  Dimensions (Nominal)  Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm  Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  35mm  Switched Poles  N/A  IP Rating  IP2XD  Contact Gap Minimum  N/A  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  EuroFix Additional Notes  TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet  Frequencies 1  All products listed conform to current British or European standard and the product Information is correct at the time of going to press.  All products listed conform to current British or European standard and the product Information is correct at the time of going to press.	Item Image	EMC Gasket  Conductor Terminal Screw  Correct position of conductor, screening	Hemilton LINEA DUO CFX DTVM Non-Isolated TV (male)	
Plate Finish Linear-Duo CFX Etrium Bronze Frame/Etrium Bronze Insert Colour Black EAN13 Barcode 5017504039202 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Is x 4mm2 Multi-strand Earth Terminal Capacity 4 Ix 4mm2 Multi-strand Earth Terminal Capacity 5 Ix 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m EuroFix Additional Notes TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet Frequencies 1 FM DC-5-2200 MHz Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Disping certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press.	Primary Range	Linea-Duo CFX		
Insert Colour  Black  EAN13 Barcode  5017504039202  Dimensions (Nominal)  Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm  Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  35mm  Switched Poles  N/A  IP Rating  IP ZXD  Contact Gap Minimum  N/A  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  1 x 4mm2 Multi-strand  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Maximum Installation Altitude  2000m  EuroFix Additional Notes  TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet  Frequencies 1  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited ES EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and midmension withou prior notice.	Insert Type			
EAN13 Barcode  5017504039202  Dimensions (Nominal)  Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm  Fixing Hole Centres  80x Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth 35mm  Switched Poles  N/A  IP Rating IP2XD  Contact Gap Minimum N/A  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5" to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude  2000m  EuroFix Additional Notes  TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet  Frequencies 1  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.	Plate Finish			
Dimensions (Nominal)   Single: Height = 86.0mm   Width = 86.0mm   Depth = 4.0mm	Insert Colour	Black		
Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  35mm  N/A  IP Rating  IP2XD  Contact Gap Minimum  N/A  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  EuroFix Additional Notes  TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet  Frequencies 1  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Box Fixing = 60.3mm Grid Fixing = CFX Clips  N/A  Smm  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Box Fixing = 60.3mm Grid Fixing = CFX Clips  N/A  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Box Fixing = CFX Clips  N/A  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Box Fixing = CFX Clips  All approducts listed conform to current British or European standard and the product information is correct at the time of going to press.  Box Fixing = CFX Clips  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Box Fixing = CFX Clips  All products listed conform to current British or European standard and the product information is an admensions without prior notice.	EAN13 Barcode	5017504039202		
Minimum Wall Box Depth  35mm  N/A  IP Rating  IP SXD  Contact Gap Minimum  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 6  1 x 6mm2  Product Class 1  Must be earthed (ref BS7671 415.2.1)  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  EuroFix Additional Notes  TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet  Frequencies 1  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited  It is the policy of the company to improve products  as part of our development programme. Therefore, we reserve the right to after designs and dimensions without prior notice.	Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm		
Switched Poles N/A  IP Rating IP2XD  Contact Gap Minimum N/A  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed (ref BS7671 415.2.1)  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  EuroFix Additional Notes TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet  Frequencies 1 FM DC=5-2200 MHz  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  Linea is a Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.	Fixing Hole Centres			
IP Rating	Minimum Wall Box Depth			
Contact Gap Minimum N/A  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed (ref BS7671 415.2.1)  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Maximum Installation Altitude 2000m  EuroFix Additional Notes TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet  Frequencies 1 FM DC=5-2200 MHz  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice.	Switched Poles	N/A		
Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed (ref BS7671 415.2.1)  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  EuroFix Additional Notes TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet  Frequencies 1 FM DC=5-2200 MHz  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	IP Rating	IP2XD		
Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  EuroFix Additional Notes  TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet  Frequencies 1  FM DC=5-2200 MHz  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Earth Terminal Capacity 3  3 x 2.5mm2  1 x 4mm2 Multi-strand  1 x 4mm2 Multi-strand  1 x 4mm2 Multi-strand  1 x 4mm2 Multi-strand  2 x 4 x 1.5mm2  1 x 4mm2 Multi-strand  2 x 4 x 1.5mm2  4 x 4 mm2 Multi-strand  2 x 4 x 1.5mm2  4 x 4 mm2 Multi-strand  2 x 4 x 1.5mm2  4 x 4 mm2 Multi-strand  2 x 4 x 1.5mm2  4 x 4 mm2 Multi-strand  2 x 4 x 4.5mm2  4 x 4 mm2 Multi-strand  2 x 4 x 1.5mm2  4 x 4 mm2 Multi-strand  3 x 2.5mm2  4 x 4 mm2 Multi-strand  4 x 4 mm2 Multi-strand  4 x 4 mm2 Multi-strand  4 x 6 mm2  FM DC=5-2.01  FM DC=5-2.00 MHz  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All accessories are manufactured under an accredited  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	Contact Gap Minimum	N/A		
Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  EuroFix Additional Notes  Frequencies 1  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  3 x 2.5mm2  1 x 4mm2 Multi-strand  2 x 4mm2 Multi-strand  1 x 4mm2 Multi-strand  1 x 4mm2 Multi-strand  2 x 4mm2 Multi-strand  1 x 4mm2 Multi-strand  1 x 4mm2 Multi-strand  2 x 4mm2 Multi-strand  2 x 4mm2 Multi-strand  3 x 2.5mm2  4 x 4mm2 Multi-strand  5 x 6 x 4mm2  4 x 4mm2 Multi-strand  4 x 4mm2 Multi-strand  5 x 4mm2 Multi-strand  4 x 4mm2 Multi-strand  5 x 4mm2 Multi-strand  5 x 6 x 4mm2  7 x 4mm2 Multi-strand  5 x 4mm2 Must be earthed (ref BS7671 415.2.1)  4 x 4mm2 Must be earthed (ref BS7671 415.2.1)  4 x 4mm2 Must be earthed (ref BS7671 415.2.1)  4 x 4mm2 Must be earthed (ref BS7671 415.2.1)  4 x 4mm2 Must be earthed (ref BS7671 415.2.1)  5 x 4mm2 Must be earthed (ref BS7671 415.2.1)  5 x 4mm2 Must be earthed (ref BS7671 415.2.1)  5 x 4mm2 Must be earthed (ref BS7671 415.2.1)  5 x 4mm2 Must be earthed (ref BS7671 415.2.1)  5 x 4mm2 Must be earthed (ref BS7671 415.2.1)  5 x 4mm2 Must be earthed (ref BS7671 415.2.1)  6 x 4mm2 Must be earthed (ref BS7671 415.2.1)  6 x 4mm2 Must be earthed (ref BS7671 415.2.1)  6 x 4mm2 Must be earthed (ref BS7671 415.2.1)  6 x 4mm2 Must be earthed (ref BS7671 415.2.1)  6 x 4mm2 Must be earthed (ref BS7671 415.2.1)  7 x 4mm2 Must be earthed (re	Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Must be earthed (ref BS7671 415.2.1)  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  EuroFix Additional Notes  TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet  Frequencies 1  Patents and Trademarks  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 5  Product Class 1  Must be earthed (ref BS7671 415.2.1)  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  EuroFix Additional Notes  TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet  Frequencies 1  FM DC=5-2200 MHz  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  EuroFix Additional Notes  TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet  Frequencies 1  FM DC=5-2200 MHz  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  EuroFix Additional Notes  TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet  Frequencies 1  FM DC=5-2200 MHz  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  EuroFix Additional Notes TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet  Frequencies 1 FM DC=5-2200 MHz  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	Product Class 1	Must be earthed (ref BS7671 415.2.1)		
Maximum Installation Altitude  EuroFix Additional Notes  TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet  Frequencies 1  FM DC=5-2200 MHz  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or  European standard and the product information is  correct at the time of going to press.  All accessories are manufactured under an accredited  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	Ambient Operating Temperature	-5° to +40°C		
EuroFix Additional Notes  TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet  Frequencies 1  FM DC=5-2200 MHz  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	Recommended Location	Internal Use Only		
Frequencies 1  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	Maximum Installation Altitude	2000m		
Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or  European standard and the product information is  correct at the time of going to press.  All accessories are manufactured under an accredited  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	EuroFix Additional Notes	TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet		
Patents and Trademarks  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	Frequencies 1	FM DC=5-2200 MHz		
European standard and the product information is correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174		
Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 15 October 2018 08:18	European standard and the product information is		as part of our development programme.  Therefore, we reserve the right to alter designs	
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 15 October 2018 08:18 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)1779 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84











