Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio LDDTVMSB-SSB Linea-Duo CFX Satin Brass Frame/Satin Steel Front 1 gang Non-Isolated TV (Male) Black Item Image Wiring Dimensions Hemilton LINEA DUO CFX DTVM Non-Isolated TV (male) EMC Gasket 86 ((0) - 25.0 Conductor Terminal Screw 50.0 Correct position of conductor, screening braid and cable Primary Range Linea-Duo CFX Insert Type 1 gang Non-Isolated TV (Male) (DAB Compatible) Plate Finish Linea-Duo CFX Satin Brass Frame/Satin Steel Insert Colour Black EAN13 Barcode 5017504161514 Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Dimensions (Nominal) **Fixing Hole Centres** Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Must be earthed (ref BS7671 415.2.1) Product Class 1 -5° to +40°C Ambient Operating Temperature Internal Use Only Recommended Location Maximum Installation Altitude 2000m EuroFix Additional Notes TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet Frequencies 1 FM DC=5-2200 MHz Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products BS EN ISO 9001 : 2015 Quality Management System European standard and the product information is as part of our development programme correct at the time of going to press Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 15 October 2018 08:18 AM Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE process and are not binding. of certain finishes. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ Listed in STrimble T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84 LUCKINS

SL