Hamilton

making connections beautifully

SL

| Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio | | | |
|---|---|--|--|
| | LDEURO2PB-BS | | |
| Linea-Duo CFX EuroFix Polished Brass I | Frame/Bright Steel Front Single Plate complet Grid | te with 2 EuroFix Apertures 50x50mm and | |
| Item Image | Wiring | Dimensions | |
| | | LINEA DUO CFX EURO2 Single plate with 2 x EuroFix cutout | |
| | | | |
| Primary Range | EuroFix | | |
| Insert Type | 2 Gang EuroFix 50x50mm Apertured Plate with Grid | | |
| Plate Finish | Linea-Duo CFX EuroFix Polished Brass Frame/Bright Steel | | |
| Insert Colour | No Insert Colour | | |
| EAN13 Barcode | 5017504139179 | | |
| Dimensions (Nominal) | Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm | | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | | |
| Minimum Wall Box Depth | As Per Inserts | | |
| Switched Poles | N/A | | |
| IP Rating | N/A | | |
| Contact Gap Minimum | N/A | | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | | |
| Earth Terminal Capacity 2 | 4x1.5mm2 | | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | | |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand | | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | | |
| Product Class 1 | Face plate must be earthed | | |
| Recommended Location | Internal Use Only | | |
| Maximum Installation Altitude | 2000m | | |
| Additional Notes | See EuroFix for a full range of inserts. Plates must be Earthed via the Earth Tag. | | |
| Patents and Trademarks | EuroFix is a Registered Trade Mark No. 2560270 | | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. | |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 15 October 2018 09:03 Al E&O | |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville F T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com Registered | Road, Brislington, Bristol, BS4 5NZ Office 1 Rushmilts, Bedford Road, Northampton NN4 7YB in London No. 941624 VAT Registration No. 222 6607 84 | Listed in Trimble LUCKINS Rector INSTRUE | |