SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LDJ12BC-BSB

Linea-Duo CFX Bright Chrome Frame/Bright Steel Front 1 gang RJ12 Outlet - Unshielded Black			
Item Image	Wiring	Dimensions	
	Distacom Module Rear View RJ11 / 12 Socket Rear View Cable tie anchor SSS_BJ11 / 12 Witten Coder Codes TO USE TO	LINEA DUO GFX J12 1 gang RJ12 Outlet Unshielded 6 wire	
Primary Range	Linea-Duo CFX		
Insert Type	1 gang RJ12 Outlet - Unshielded		
Plate Finish	Linea-Duo CFX Bright Chrome Frame/Bright Steel		
Insert Colour	Black		
EAN13 Barcode	5017504201555		
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm		
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Minimum Wall Box Depth	35mm		
Switched Poles	N/A		
IP Rating	IP2XD		
Contact Gap Minimum	N/A		
Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 5	1 x 6mm2		
Product Class 1	Must be earthed (ref BS7671 415.2.1)		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
EuroFix Additional Notes	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)		
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 08:18 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











