SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LDJ12SB-SBB

Linea-Duo CEX Satin Brass Frame/Satin Brass Front 1 gang R.112 Outlet - Unshielded Black

| Linea-Duo CFX Satin Brass Frame/Satin Brass Front 1 gang RJ12 Outlet - Unshielded Black                                    |  |   |
|--|--|---|
| Item Image   | Detacom Module Rear View RU11 12 Socket Rear View Q12 7 4 5 9 9 Q12 7 5 9 9 Q12 7 5 9 9 Q12 7 7 7 7 7 7 9 Q12 7 7 7 7 7 7 9 Q12 7 7 7 7 7 7 9 Q12 7 7 7 7 7 7 7 9 Q12 7 7 7 7 7 7 7 9 Q12 7 7 7 7 7 7 7 7 9 Q12 7 7 7 7 7 7 7 7 7 7 7 7 9 Q12 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7  | Dimensions  Hamilton LINEA DUO CFX  J12 1 gang RJ12 Outlet Unshielded 6 wire  |
| Primary Range  | Linea-Duo CFX  |   |
| Insert Type  | 1 gang RJ12 Outlet - Unshielded  |   |
| Plate Finish   | Linea-Duo CFX Satin Brass Frame/Satin Brass  |   |
| Insert Colour  | Black  |   |
| EAN13 Barcode  | 5017504151553  |   |
| Dimensions (Nominal)   | Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm   |   |
| Fixing Hole Centres  | Box Fixing = 60.3mm Grid Fixing = CFX Clips  |   |
| Minimum Wall Box Depth   | 35mm   |   |
| Switched Poles   | N/A  |   |
| IP Rating  | IP2XD  |   |
| Contact Gap Minimum  | N/A  |   |
| Earth Terminal Capacity 1  | 5 x 1mm2   |   |
| Earth Terminal Capacity 2  | 4 x 1.5mm2   |   |
| Earth Terminal Capacity 3  | 3 x 2.5mm2   |   |
| Earth Terminal Capacity 4  | 1 x 4mm2 Multi-strand  |   |
| Earth Terminal Capacity 5  | 1 x 6mm2   |   |
| Product Class 1  | Must be earthed (ref BS7671 415.2.1)   |   |
| Ambient Operating Temperature  | -5° to +40°C   |   |
| Recommended Location   | Internal Use Only  |   |
| Maximum Installation Altitude  | 2000m  |   |
| EuroFix Additional Notes   | Can be used as either RJ11 (4 wires) or RJ12 (6 wires)   |   |
| Patents and Trademarks  All products listed conform to current British or European standard and the product information is | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174  All accessories are manufactured under an accredited  RS FUISO 2004 2345 Quality Management System  RS F |   |
| European standard and the product information is correct at the time of going to press.                                    | BS EN ISO 9001 : 2015 Quality Management System.   | as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  | Correct as at 15 October 2018 08:18 AM<br>E&OE  |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











