

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

the limitations of reproduction and printing guarantee an exact colour match and shadings of E&	LDK21PB-BSB			
Primary Range Linear Durs CFX Insert Type Ingang 200X 2 Way Key Switch Insert Colour Bask EAN13 Barcode Donrations Riverniae) Songe: Hught = 86.0mm Width = 86.0mm Depth = 4.0mm Demarkors Riverniae) Songe: Hught = 86.0mm Width = 86.0mm Depth = 4.0mm Depth =	Linea-Duo CFX Polished Brass Frame/Bright Steel Front 1 gang 20AX 2 Way Key Switch Black			
Primary Range Linea-Duo CFX Insent Type 1 gang 20AX 2 Way Key Switch Insent Type 1 gang 20AX 2 Way Key Switch Insent Type 1 gang 20AX 2 Way Key Switch Insent Type 1 gang 20AX 2 Way Key Switch Insent Type 1 gang 20AX 2 Way Key Switch Insent Type 1 gang 20AX 2 Way Key Switch Insent Type Insent Type 1 gang 20AX 2 Way Key Switch Insent Type Ins				
Primary Range Insert Type 1 gang 20AX 2 Way Key Switch Insert Type 1 gang 20AX 2 Way Key Switch Insert Type 1 gang 20AX 2 Way Key Switch Insert Colour Black EAN13 Barcode 5017504132699 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 38mm Switched Polas Single Current Rainig 20AX Voltage 220250V AC Maximum Load 30 Amp Inductive Mains Firequency 50Hz PRating PP2XO Contact Gap Minimum 3mm Firequency 50Hz Terminal Capacity 3 5x 1mm2 Terminal Capacity 1 5x 1mm2 Terminal Capacity 4 1 x 6.5mm2 Terminal Capacity 4 1 x 6.5mm2 Terminal Capacity 4 1 x 6.5mm2 Earth Terminal Capacity 1 5 x 1 fmm2 Terminal Capacity 1 5 x 1 fmm2 Terminal Capacity 1 5 x 1 fmm2 Terminal Capacity 5 1 x 6 mm2 Earth Terminal Capacity 7 5 x 1 fmm2 Earth Terminal Capacity 6 1 x 6 mm2 Earth Terminal Capacity 7 5 x 1 fmm2 Earth Terminal Capacity 6 1 x 6 mm2 Earth Terminal Capacity 6 1 x 6 mm2 Earth Terminal Capacity 7 Earth Terminal Capacity 6 1 x 6 mm2 Earth Terminal Capacity 7 Earth Terminal Capacity 7 Earth Terminal Capacity 6 1 x 6 mm2 Earth Terminal Capacity 7 Earth Terminal Capacity 6 1 x 6 mm2 Earth Terminal Capacity 7 Earth Terminal Capacity 6 1 x 6 mm2 Earth Terminal Capacity 7 Earth Terminal Capacity 6 1 x 6 mm2 Earth Terminal Capacity 7 Earth Terminal Capacity 6 1 x 6 mm2 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Ea			LINEA DUO CFX K21	
Insert Type		Abstractive 2 vary eventuring Long in Lucys Out Intermediate sectoring		
Insert Colour Black Insert Colour Black EAN13 Barcode 5017504132699 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Exing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load Mains Frequency 50Hz P Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x tmm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 2x 2.5mm2 Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 5x 1.5mm2 Earth Terminal Capacity 5 5x 1.5mm2 Earth Terminal Capacity 6 5x 1.5mm2 Earth Terminal Capacity 7 5x 1.5mm2 Earth Terminal Capacity 8 5x 1.5mm2 Earth Terminal Capacity 9 5x 1.5mm2 Earth Terminal Capacity 1 5x 1.5mm2 Earth Terminal	Primary Range	Linea-Duo CFX		
Insert Colour EAN13 Barcode 5017504132699 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Exing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX Vottage 220/250V AC Maximum Load 20 Amp inductive Mans Frequency 50Hz IP Rating IP Rating IP PXD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 4 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Capacity 7 Earth Capacity 7 Earth Capacity 7 Eart	Insert Type	1 gang 20AX 2 Way Key Switch		
EAN13 Barcode Sol17504132699 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm	Plate Finish	Linea-Duo CFX Polished Brass Frame/Bright Steel		
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Pixing Pole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Simm Switched Poles Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 10 Rating IPEXD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 2 x 4 x 1.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Ferril Perril Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal	Insert Colour	Black		
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating Parting Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 2 5x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 6 Earth Terminal Capacity 9 Earth Terminal Capacity	EAN13 Barcode	5017504132699		
Minimum Wall Box Depth Switched Poles Single Current Rating 20AX Voltage 220250V AC Maximum Load 20 Amp inductive Mains Frequency SoHz Preminal Capacity 1 So X mm2 Terminal Capacity 1 So X mm2 Terminal Capacity 1 So X mm2 Terminal Capacity 3 Zo X .5mm2 Terminal Capacity 3 Zo X .5mm2 Terminal Capacity 4 Zo X .5mm2 Terminal Capacity 4 Zo X .5mm2 Terminal Capacity 5 Zo X .5mm2 Zo X .5m	Dimensions (Nominal)	·		
Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 2x 2.5mm2 Terminal Capacity 4 1x 6mm2 Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 6x 1mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 5x 1.5mm2 Earth Terminal Capacity 3 5x 1.5mm2 Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 5x 1.5mm2 Earth Terminal Capacity 6 5x 1.5mm2 Earth Terminal Capacity 7 5x 1.5mm2 Earth Terminal Capacity 8 5x 2.5mm2 Earth Terminal Capacity 8 5x 2.5mm2 Earth Terminal Capacity 9 5x 2.5mm2 Earth Terminal Capacity 9 5x 2.5mm2 Earth Terminal Capacity 6 5x 2.5mm2 Earth Terminal Capacity 7 5x 2.5mm2 Earth Terminal Capacity 8 5x 2.5m	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Current Rating 20AX Voltage 220/250V AC Asximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Ferminal Capacity 1 5 x 1 mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 2 x 4 mm2 Multi-strand Terminal Capacity 4 1 x 6 mm2 Earth Terminal Capacity 5 1 x 6 mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 4 2 x 4 mm2 Multi-strand Earth Terminal Capacity 5 1 x 6 mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 1 Earth Terminal Capacity 9 Earth Terminal Capacity 1 Earth Terminal Capacity 9 Earth Termi	Minimum Wall Box Depth	35mm		
Voltage 220/250 V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Forduct Class 1	Switched Poles	Single		
Maximum Load 20 Amp inductive Mains Frequency IP Rating IP Rat	Current Rating	20AX		
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1.mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 2x 2.5mm2 Terminal Capacity 4 2x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 6x 1.mm2 Earth Terminal Capacity 1 5x 1.5mm2 Earth Terminal Capacity 2 5x 1.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 1x 6mm2 Earth Terminal Capacity 4 2x 4mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 1x 6mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. CB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 8:19, guarantee an exact colour match and shadings of	Voltage	220/250V AC		
IP Rating	Maximum Load	20 Amp inductive		
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 4 Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth T	Mains Frequency	50Hz		
Terminal Capacity 2 Terminal Capacity 2 Terminal Capacity 3 Z x 2.5mm2 Terminal Capacity 4 Z x 4mm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature 4.5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. BLINEATION OF A 15 and Conform to current British or European standard and the product information is correct at the time of going to press. Due to manufacturing processes we cannot Therefore, we reserve the right to alter designs and dimensions without prior notice. Example 1 Example 2 Example 2 Example 3 Example 3 Example 3 Example 3 Example 4 Example 3 Example 4 E	IP Rating	IP2XD		
Terminal Capacity 2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9	Contact Gap Minimum	3mm		
Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 4 Terminal Capacity 6 Terminal Capacity 6 Terminal Capacity 8 Terminal Capacity 9	Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 4 2 x 4mm2 Multi-strand 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Termina	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal	Terminal Capacity 3	2 x 2.5mm2		
Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks Linea-Duo CFX is a UK Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Bllustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:19. Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 x 2.5mm2 Earth Terminal Capacity 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Cap	Terminal Capacity 4	2 x 4mm2 Multi-strand		
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:19.	Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval Earth Terminal Capacity 5 Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Bllustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:19. E&	Earth Terminal Capacity 1	6 x 1mm2		
Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Must be earthed Jone 1 Aminomal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-1 Patents and Trademarks Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. But to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:19. Example 1 Linea is a Registered Trade Mark No 2398667 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:19. Example 1 Example 2 Example 3 Example 3 Example 3 Example 4	Earth Terminal Capacity 2	5 x 1.5mm2		
Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:19. Correct as at 15 October 2018 08:19. E&	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:19 guarantee an exact colour match and shadings of	Earth Terminal Capacity 4	2 x 4mm2 Multi-strand		
Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:19 E&	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:19 E&	Product Class 1	Must be earthed		
Maximum Installation Altitude Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:19 E&	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:19 E&	Recommended Location	Internal Use Only		
Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 15 October 2018 08:19 E& Correct as at 15 October 2018 08:19 E&	Maximum Installation Altitude	2000m		
Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 08:19. E&	Standard/Approval	BS EN 60669-1		
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E&	Patents and Trademarks	Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B		
the limitations of reproduction and printing guarantee an exact colour match and shadings of E&	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
process and are not uniquing. Or certain missines.			Correct as at 15 October 2018 08:19 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio