

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LDK21PB-PBW		
Linea-Duo CFX Polished Brass Frame/Polished Brass Front 1 gang 20AX 2 Way Key Switch White		
Item Image	Wiring	Dimensions
	Alternative 2 very swifting  Less pin Lone Out  Less pin Lone Out  Sternmendate swifting	Hemiton LINEA DUO CFX K21 2 Way Key switch
Primary Range	Linea-Duo CFX	
Insert Type	1 gang 20AX 2 Way Key Switch	
Plate Finish	Linea-Duo CFX Polished Brass Frame/Polished Brass	
Insert Colour	White	
EAN13 Barcode	5017504103699	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	Single	
Current Rating	20AX	
Voltage	220/250V AC	
Maximum Load	20 Amp inductive	
Mains Frequency	50Hz IP2XD	
IP Rating		
Contact Gap Minimum	3mm 5 x 1mm2	
Terminal Capacity 1	5 x 1mm2 4 x 1.5mm2	
Terminal Capacity 2	2 x 2.5mm2	
Terminal Capacity 3	2 x 2.5mm2 2 x 4mm2 Multi-strand	
Terminal Capacity 4	2 x 4mm2 Multi-strand  1 x 6mm2	
Terminal Capacity 5	1 x 6mm2 6 x 1mm2	
Earth Terminal Capacity 1	6 x 1mm2 5 x 1.5mm2	
Earth Terminal Capacity 2	3 x 2.5mm2	
Earth Terminal Capacity 4	2 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Earth Terminal Capacity 5 Product Class 1	Must be earthed	
	-5° to +40°C	
Ambient Operating Temperature  Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-1	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 08:19 AM E&OE
	The second secon	riba bei Iso

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio