

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

Voltage 20/250 V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1 mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 6 5 x 4 mm2 Earth Terminal Capacity 6 5 x 4 mm2 Earth Terminal Capacity 6 5 x 6 x 6 x 6 x 6 x 6 x 6 x 6 x 6 x 6	LDK21PB-SBB			
Primary Range	Linea-Duo CFX Polished Brass Frame/Satin Brass Front 1 gang 20AX 2 Way Key Switch Black			
Permary Range Linear-Duo CFX Insert Type 1 parry 20AX 2 Way Key Switch Insert Type 1 parry 20AX 2 Way Key Switch Insert Obour Black EAN13 Barcode 30,775041 22661 Black EAN13 Barcode 30,775041 22661 Black EAN13 Barcode 30,775041 22661 Black EAN15 Barcode 30,775041 22661 Black EAN16				
Primary Range Linea-Duo CFX Insert Type 1 gang 20AX 2 Way Key Switch Helse Finish Linea-Duo CFX Polished Brass Frame/Satin Brass Insert Colour Black EAN13 Barcode 5017504112891 Dimensions (Nominal) Single: Height = 86.0mm. Width = 86.0mm. Depth = 4.0mm Fixing Hole Centres Box Frame/Satin Depth = 4.0mm Fixing Hole Centres Fixing Hole C			LINEA DUO CFX K21 2 Way Key switch	
Insert Type		Attenuito 2 very setting Lore in Lore Out Attenuito 2 very setting	86.0	
Piete Finish	Primary Range	Linea-Duo CFX		
Black	Insert Type	1 gang 20AX 2 Way Key Switch		
EAN13 Barcode Single: Height = 86.mm Width = 86.mm Depth = 4.0mm Finig Hole Centres Box Finig = 80.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Single Minimum Wall Box Depth Single Current Rating 20AX Voltage 220/250V AC Maximum Load Maximum Load Maximum Load Maximum Load Maximum Load Pextor Pextor Pextor Pextor Pextor Pextor Pextor Pextor Single Cortact Gap Minimum Single Pextor Cortact Gap Minimum Single Pextor Pextor Perminal Capacity 1 5 x tmm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 2 x 5.5mm2 Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 6 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature Ambient Operating Temperature Extra Cortact of the International Capacity 6 x 1.5mm2 Earth Terminal Capacity 6 x 1.5mm2 Earth Terminal Capacity 6 x 1.5mm2 Earth Terminal Capacity 7 x 1.5mm2 Earth Terminal Capacity 8 x 1.5mm2 Earth Terminal Capacity 8 x 1.5mm2 Earth Terminal Capacity 9 x 1.5mm2 Earth Terminal Capacity 6 x 1.5mm2 Earth Terminal Capacit	Plate Finish	Linea-Duo CFX Polished Brass Frame/Satin Brass		
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Box Fixing = 60.3mm Grid Fixing = CFX Clips Switched Poles Single Current Rating 20AX Voltage 20AZ Voltage Maximum Load 20 Amp inductive Mains Frequency 15 PAZING Cortect Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 4 5 x 1mm2 Terminal Capacity 5 5 x 1mm2 Terminal Capacity 6 5 x 1mm2 Terminal Capacity 6 5 x 1mm2 Terminal Capacity 7 5 x 1mm2 Terminal Capacity 7 5 x 1mm2 Terminal Capacity 8 5 x 1mm2 Terminal Capacity 9 5 x 1.5mm2 Terminal Capacity 9 5 x	Insert Colour	Black		
Box Fixing = 60.3mm Grid Fixing = CFX Clips	EAN13 Barcode			
Mnimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Arnbient Operating Temperature .5* to 440***C Recommended Location Internal Use On	Dimensions (Nominal)	· ·		
Switched Poles Current Rating 20AX 220/250V AC Maximum Load 220/250V AC Maximum Load 20 Amp inductive Sohle IP Rating IP Rat	Fixing Hole Centres			
Current Rating 20AX Voltage 220/250 V AC Maximum Load 20 Amp Inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ms be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 200m Standard/Approval 8S EN 6069-1 Fates as Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Line	Minimum Wall Box Depth			
Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 1 5x 1mm2 Terminal Capacity 3 2x 2.5mm2 Terminal Capacity 4 2x 4.5mm2 Terminal Capacity 5 1 1x 6mm2 Earth Terminal Capacity 1 6x 1mm2 Earth Terminal Capacity 5 1 5x 1.5mm2 Earth Terminal Capacity 1 6x 1.5mm2 Earth Terminal Capacity 5 1 1x 6mm2 Earth Terminal Capacity 6 1 1x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5° 10 + 40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Earth Earth Standard Amplemarks Capacity 6 1 Linea is a Registered Trade Mark No 2398665 Patents and Trademarks Capacity 6 1 Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No. R21 = 3021173 SS2 = 3021174 It is the policy of the company to improve products as part of our development programme. BS EN ISO 9001: 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Excorrect at the time of gioing to press. Illustrations and diagrams are reproduced within the limitations of reproduction and printing variance an exact colour match and shadings of or certain finishes.	Switched Poles			
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 5 x 1.5mm2 Earth Terminal Capacity 8 1 x 6mm2 Earth Terminal Capacity 9 5 x 1.5mm2 Earth Terminal Capacity 9 5 x 1.5mm2 Earth Terminal Capacity 9 5 x 4.5mm2 Earth Terminal Capacity 9 x 4 x 4.5mm2 Earth Terminal Capa	Current Rating			
Mains Frequency Patting Patting	Voltage			
P Rating	Maximum Load	20 Amp inductive		
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal C	Mains Frequency			
Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark	IP Rating	IP2XD		
Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature .5° to +40°C Maximum Installation Altitude .2000m Maximum Installation Altitude .2000m Standard/Approval BS EN 60669-1 Fatents and Trademarks .Created and the product information is current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Due to manufacturing processes we cannot the limitations of reproduction and printing processes we cannot certain finish or earth of certain finishs or derent information is guarantee on exact colour match and shadings of certain finishs or certain finish or certain finishs or certain finish or certain finishs or certain	·			
Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 6x 1.5mm2 Earth Terminal Capacity 2 5x 1.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 4 2x 4mm2 Multi-strand Earth Terminal Capacity 4 2x 4mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Froduct Class 1 1x 6mm2 Froduct Class 1x 6mm2 Froduct Class 1 1x 6mm2 Froduct Class 1x 6mm2 Froduct				
Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of correct as at 15 October 2018 08:19 AM ESOE				
Terminal Capacity 5	Terminal Capacity 3			
Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited European standard and the product information is correct at the time of going to press. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 15 October 2018 08:19 AM E&OE	Terminal Capacity 4			
Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BLINEATOR OF AUGUSTAN AND	Terminal Capacity 5			
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature 7-5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BUS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Earth Terminal Capacity 1			
Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN 150 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Earth Terminal Capacity 2	5 x 1.5mm2		
Earth Terminal Capacity 5 1	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Bue to manufacturing processes we cannot guarantee an exact colour match and shadings of process and are not binding. Correct as at 15 October 2018 08:19 AM E&OE	Earth Terminal Capacity 4	2 x 4mm2 Multi-strand		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Bullustrations and diagrams are reproduced within the limitations of reproduction and printing processes are an exact colour match and shadings of of certain finishes.	Earth Terminal Capacity 5			
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.				
Maximum Installation Altitude Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Bullustrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Ambient Operating Temperature			
Standard/Approval BS EN 60669-1		·		
Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 15 October 2018 08:19 AM E&OE				
All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 15 October 2018 08:19 AM E&OE of certain finishes.	Linea is a Registered Trade Mark No 2398665 atents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B			
the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. guarantee an exact colour match and shadings of certain finishes.	European standard and the product information is	All accessories are manufactured under an accredited	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs	
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 15 October 2018 08:19 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio