

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LDK21PB-SBW

Linea-Duo CFX Polished Brass Frame/Satin Brass Front 1 gang 20AX 2 Way Key Switch White Item Image	
Primary Range Insert Type 1 gang 20AX 2 Way Key Switch Plate Finish Linea-Duo CFX Polished Brass Frame/Satin Brass Insert Colour EAN13 Barcode Dimensions (Nominal) Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Current Rating 20AX	
Primary Range Insert Type Ingang 20AX 2 Way Key Switch Plate Finish Linea-Duo CFX Polished Brass Frame/Satin Brass Insert Colour EAN13 Barcode Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Switched Poles Current Rating 20AX	
Insert Type 1 gang 20AX 2 Way Key Switch Plate Finish Linea-Duo CFX Polished Brass Frame/Satin Brass Insert Colour White EAN13 Barcode 5017504113698 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX	16.0
Plate Finish Linea-Duo CFX Polished Brass Frame/Satin Brass Insert Colour White EAN13 Barcode 5017504113698 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX	
Insert Colour White EAN13 Barcode 5017504113698 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX	
EAN13 Barcode 5017504113698 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX	
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX	
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX	
Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX	
Switched Poles Single Current Rating 20AX	
Current Rating 20AX	
· ·	
Voltage 220/250V AC	
Maximum Load 20 Amp inductive	
Mains Frequency 50Hz	
IP Rating IP2XD	
Contact Gap Minimum 3mm	
Terminal Capacity 1 5 x 1mm2	
Terminal Capacity 2 4 x 1.5mm2	
Terminal Capacity 3 2 x 2.5mm2	
Terminal Capacity 4 2 x 4mm2 Multi-strand	
Terminal Capacity 5 1 x 6mm2	
Earth Terminal Capacity 1 6 x 1mm2	
Earth Terminal Capacity 2 5 x 1.5mm2	
Earth Terminal Capacity 3 3 x 2.5mm2	
Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	
Earth Terminal Capacity 5 1 x 6mm2	
Product Class 1 Must be earthed	
Ambient Operating Temperature -5° to +40°C	
Recommended Location Internal Use Only	
Maximum Installation Altitude 2000m	
Standard/Approval BS EN 60669-1	
Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Duo CFX is a UK Registered Design Certificate No: R21 = 3021173 SS2 = 3021174	
All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter and dimensions without prior now.	nme. designs
Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio