

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LDKELPB-SSB

Item Image Wiring Primary Range Linea-Duo CFX Insert Type Plate Finish Linea-Duo CFX Polished Brass Fra Insert Colour Black	Dimensions Hemilton LINEADUOCTX KEL 2 Way Key switch EMG LTG TEST 86.0
Primary Range Linea-Duo CFX Insert Type 1 gang 20AX 2 Way Key Switch EI Plate Finish Linea-Duo CFX Polished Brass Fra	EMG LTG TEST
Insert Type 1 gang 20AX 2 Way Key Switch El Plate Finish Linea-Duo CFX Polished Brass Fra	
Plate Finish Linea-Duo CFX Polished Brass Fra	
	rame/Satin Steel
Insert Colour Black	
EAN13 Barcode 5017504142100	
Dimensions (Nominal) Single: Height = 86.0mm Width	•
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing	g = CFX Clips
Minimum Wall Box Depth 35mm	
Switched Poles Single	
Current Rating 20AX	
Voltage 220/250V AC	
Maximum Load 20 Amp inductive	
Mains Frequency 50Hz	
IP Rating IP2XD	
Contact Gap Minimum 3mm	
Terminal Capacity 1 5 x 1mm2	
Terminal Capacity 2 4 x 1.5mm2	
Terminal Capacity 3 2 x 2.5mm2	
Terminal Capacity 4 2 x 4mm2 Multi-strand	
Terminal Capacity 5 1 x 6mm2	
Earth Terminal Capacity 1 6 x 1mm2	
Earth Terminal Capacity 2 5 x 1.5mm2	
Earth Terminal Capacity 3 3 x 2.5mm2	
Earth Terminal Capacity 4 2 x 4mm2 Multi-strand	
Earth Terminal Capacity 5 1 x 6mm2	
Product Class 1 Must be earthed	
Ambient Operating Temperature -5° to +40°C	
Recommended Location Internal Use Only	
Maximum Installation Altitude 2000m	
Standard/Approval BS EN 60669-1	
	: No 2398665 No 2398667 Patent No. GB 2383375B ad Design Certificate No: R21 = 3021173 SS2 = 3021174
All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufacture BS EN ISO 9001 : 2015 Quality	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour maprocess and are not binding. Due to manufacturing process guarantee an exact colour maprocess and are not binding.	natch and shadings of E&C

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio